Uniform Network Code Validation Rules

Version 2.3 DRAFT

Deleted: 3

michele.downes 20/9/13 15:21

Deleted: 0

© all rights reserved

All rights reserved. No part of this document may be reproduced, stored or transmitted without the written permission of the

Transporters.

UNCVR

Version 2.3, 15/10/2013

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Deleted: 07

michele.downes 8/10/13 12:32 Deleted: 20

michele.downes 8/10/13 12:32 Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

Document Control

Version	Date	Reason for Change
2.3	15/10/2013	Further updates following review
2.2	07/10/2013	Further updates following review at PN UNC on 30/09/2013
<u>2.1</u>	20 September 2013	<u>Updates following Project Nexus</u> <u>requirements</u>
2.0	20 January 2011	Clause 4 amended as a result of implementation of UNC0224, introduction and Document Control added.
1.0	05 July 2006	Rules established

Development of Rules

(a) Section M<u>5.3.3</u> of the Transportation Principal Document (TPD) of the Uniform Network Code (UNC). specifies that:

"The "Uniform Network Code Validation Rules" (or "Validation Rules") are the rules and procedures contained in the document issued by the Transporters at the [Nexus Implementation Date] and so entitled and governed and amended in accordance with Section V12 unless the Authority shall upon application by any User made within one month after such notice, give Condition A11(18) Disapproval to the Transporters making any amendment in accordance with the provisions of Section V12."

(b) The requirement to publish the Uniform Network Code Validation Rules is specified in Section V12.1(b) of the TPD of the UNC. This section also provides for the document to be published and revised from time to time. The provision (TPD V12.2) reads:

"Each Document shall be kept up to date and published by the Transporters on the Joint Office of Gas Transporters' website."

- (c) The Rules set out below meet the Transporters' obligation to prepare Guidelines, while the Document Control Section records changes which have been made to the Guidelines. The document is published on the Joint Office of Gas Transporters' website, www.gasgovernance.com.
- (d) These Guidelines can only be modified in accordance with the requirements set out in paragraph 12 of Section V of the UNC Transportation Principal Document, which reads as follows:

Emma Smith 11/7/13 09:25

Deleted: 1.5.3

Emma Smith 11/7/13 09:26

Deleted: UNC Implementation Date

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Deleted: 07

michele.downes 8/10/13 12:32

Deleted: 20 michele.downes 8/10/13 12:32

Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

Version 2.3.15/10/2013.

© all rights reserved

UNCVR

UNIFORM NETWORK CODE – TRANSPORTATION PRINCIPAL DOCUMENT

SECTION V - GENERAL

12 GENERAL PROVISIONS RELATING TO UNC RELATED DOCUMENTS

12.1 Purpose

The purpose of this Section is to establish generic governance arrangements in respect of the following UNC Related Documents (each a "Document" and collectively the "Documents"):

- (a) Network Code Operations Reporting Manual as referenced in Section V9.4;
- (b) Network Code Validation Rules referenced in Section M5.3.3;
- (c) ECQ Methodology as referenced in Section Q6.1.1(c); and
- (d) Measurement Error Notification Guidelines for NTS to LDZ and LDZ to LDZ Measurement Installations as referenced in OAD Section D 3.1.5.

12.2 Publication Requirements

Each Document shall be kept up to date and published by the Transporters on the Joint Office of Gas Transporters' website.

12.3 Modifications

Should a User or Transporter wish to propose modifications to any of the Documents, such proposed modifications shall be submitted to the Uniform Network Code Committee and considered by the Uniform Network Committee or any relevant sub-committee where the Uniform Network Code Committee so decide by majority vote.

12.4 Approved Modifications

- 12.4.1 In the event that a proposed modification is approved by a majority vote of the Uniform Network Code Committee, the modification shall be implemented. Where the Uniform Network Code Committee fails to achieve majority approval the proposed modification shall be considered in accordance with the provisions set out in Section 7 of the Uniform Network Code Modification Rules unless the Uniform Network Code Committee determines otherwise.
- **12.4.2** Each revised version of a Document shall be version controlled and retained by the Transporters. It shall be made available on the Joint Office of Gas Transporters' website.

Emma Smith 11/7/13 09:27

Deleted: 1.5.3

Emma Smith 11/7/13 09:28

Deleted: <#>the Allocation of Unidentified Gas Document referenced in Section E9.1.1.

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Emma Smith 15/10/13 15:24

Deleted: 07

michele.downes 8/10/13 12:32

Deleted: 20

michele.downes 8/10/13 12:32

Deleted: 01

michele.downes 20/9/13 15:21 **Deleted:** 1

© all rights reserved UNCVR

Version 2.3.15/10/2013.

CONTENTS

1. Introduction						05
2. Meter Reading Agency HHT (On-Si	te) Val	idation.				06
Cyclic Reading Validation .						07
4. Daily Read Equipment						80
5. Non Cyclic Meter Readings						09
6. Calculated Gas Card Readings.						10
Appendix A - Round The Clock Indica: Appendix B - Tolerance Ranges .				.vo Doil	 . Value)	12 14
Appendix C – Calculated Gas Card Re	zaumy	s (Accu	mulati	ve Dali	y value)	15

michele.downes 20/9/13 15:22

Deleted:

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Emma Smith 15/10/13 15:24

Deleted: 07

michele.downes 8/10/13 12:32

Deleted: 20

michele.downes 8/10/13 12:32

Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

© all rights reserved UNCVR

1 Introduction

This is the document referred to in Section M <u>5.3</u> of the Uniform Network Code Transportation Principal Document. It does not form part of the Uniform Network Code.

Deleted: 1

1.1 This document describes the validation rules which will be applied to non-daily (Class 3 and 4) and daily metered (Class 1 and 2) meter and convertor readings and associated data before they are applied to System User and Transporter systems. All parameterised values are subject to amendment in accordance with the procedures set out in Section M 5.3.3 of the Uniform Network Code – Transportation Principal Document. Any changes will be notified to System Users.

michele.downes 20/9/13 16:03

Deleted: t

Deleted: 5

Emma Smith 11/7/13 09:29

Deleted: 1

Emma Smith 11/7/13 09:29

Deleted: 5

Emma Smith 11/7/13 09:20

Formatted: Bullets and Numbering

- 1.2 Reads from <u>Class 1</u> daily metered sites are to be validated by the Transporter in accordance with the relevant rules described herein.
- 1.3 Reads from Class 2 daily metered sites are to be validated by the System Users in accordance with the relevant rules described herein.
- 1.4 Reads provided to the Transporter by System Users from Class 3 or 4 non-daily metered sites are to be validated by System Users in accordance with the relevant rules described herein.
- The validation described in this paper will be in addition to that used to determine that the data is in accordance with the file specification and system requirements.
- The validation refers to cyclic and non-cyclic meter readings, including asset installation meter readings.
- These rules are the minimum requirement of validation that must be undertaken for readings applied to System User and Transporter systems.
- 1.8 The Transporter will undertake a 2 step validation process for all reads received:
 - 1.8.1 An initial tolerance check which can be overridden by the User,
 - 1.8.2 if the read passes this check a second outer tolerance check will be applied that can not be overidden by the User.

Emma Smith 11/7/13 09:29

Deleted: t

Emma Smith 11/7/13 09:31

Deleted: t

Emma Smith 14/8/13 09:20

Deleted:

Emma Smith 15/10/13 15:30 **Deleted:**

Emma Sr

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Deleted: 07

michele.downes 8/10/13 12:32

Deleted: 20

michele.downes 8/10/13 12:32

Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

© all rights reserved

UNCVR

2 Meter Reading Agency HHT (On Site) Validation,

- michele.downes 20/9/13 15:23
- Deleted: (does this need amending??)

2.1 Validation for this input will be performed at the time of data capture on the HHT.

- 2.2 The meter reading will be checked to ensure that it is within a specified range either side of an estimated reading. This is known as an Inner Tolerance Range (ITR). The estimated reading will be calculated using the consumption history and the AQ of the meter.
- 2.3 If the meter reading input is outside the ITR, the meter reader will be required to re-input the meter serial number. If this number is that on the HHT (the correct meter) then they will be required to re-input the reading. This confirms the accuracy of the first reading or corrects an error on the first attempted input. If the meter number differs a meter exchange will be initiated. Similar checks are to be performed on convertor readings.
- 2.4 A check will be made on the number of digits for a meter reading i.e. six digits must be input for a six dial meter. No alteration to the number of dials can be made on the HHT. Any anomalies discovered will be reported as they generally signify meter exchanges.

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Emma Smith 15/10/13 15:24

Deleted: 07
michele.downes 8/10/13 12:32

Deleted: 20

michele.downes 8/10/13 12:32

michele.downes 20/9/13 15:21

Deleted: 1

UNCVR

Version 2.3, 15/10/2013,

© all rights reserved

3 Cyclic Reading Validation

- 3.1 A completeness check to ensure all readings expected have been received, including Convertor readings where installed.
- 3.2 All meter readings will be subjected to a round the clock test to detect possible instances where a meter has made a complete revolution of the dials between readings. It will also check for negative consumptions if a meter reading follows an estimate.

The term Round the Clock (RTC) refers to the number of times the meter or convertor has gone "through the zero's" i.e. has moved from 9999 to 0001. The use of this indicator and the reading will permit the volume of gas to be calculated as well as detecting any reversal of readings following an earlier erroneous reading. A detailed explanation of the logic is given in Appendix A.

Where the cyclic reading is submitted by the User as a 'Proposing User Read' pursuant to Uniform Network Code Transportation Principal Document M1.5.2(1), the RTC test will be performed by the Transporter.

- 3.3 Validation to ensure the read follows on from a previous actual reading, and for replacement reads, less than a subsequent actual read.
- All readings supplied by System Users will be subject to tolerance 3.4 checking.
- An inner_Tolerance_validation will be applied to all cyclic reads as per <u>3.</u>5_ appenix B.
- The User may 'override' the inner tolerance check by indicating as such <u>3.</u>6_ when submitting the reading.
- 3.7 A wider tolerance check (Market Breaker check) will be applied, a reading that breaches the wider tolerance check will be rejected by the Transporter. See appendix B
- Tolerance ranges will be based on the AQ band for a Supply Meter Point. 3.8 Tolerance Ranges are shown in Appendix B.
- 3.9 Where a convertor is fitted an additional check will be performed. To ensure that the convertor is reading meter pulses correctly the following calculation will be performed.

Meter Volume - Uncorrected Convertor Volume

Deleted:

Formatted: Font:(Default) Arial, 14 pt,

michele.downes 20/9/13 15:58

Deleted: All readings supplied by System Users will be subject to tolerance checkin ... [1]

Emma Smith 15/10/13 15:33

Deleted: over-estimate

Deleted: 4.3.. k

michele downes 20/9/13 16:00

- is this just limited to 4 dial meters?

Emma Smith 14/8/13 09:25

Deleted: For consumptions up to 10, 000 cf

there will be no t...checking michele.downes 8/10/13 12:33

Deleted: ??

michele.downes 20/9/13 15:46

Deleted: 3.3a

Emma Smith 14/8/13 09:26

Deleted: .

michele.downes 20/9/13 15:5

Deleted: 4

Emma Smith 14/8/13 09:27

Deleted: For consumptions over 10,000 cf

a...further...fails

michele.downes 20/9/13 15:50

Deleted: Section 6 covers all other reads?

Emma Smith 14/8/13 09:27

Deleted: to ensure that the reading is within a wider tolerance range of the estimated reading. This will be known as the Outer Tolerance Range (OTR). If the reading fails this test it will not be applied to the system. Readings that have been confirmed as correct although outside the ITR will be applied to the system unless they fail the OTR check.

michele.downes 20/9/13 15:50

Deleted:

[4]

[2]

michele.downes 20/9/13 15:59

Deleted: 6

michele.downes 20/9/13 16:05

Formatted: Font:(Default) Arial, 8 pt

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Emma Smith 15/10/13 15:24 Deleted: 07

michele.downes 8/10/13 12:32

Deleted: 20...01...1

© all rights reserved

UNCVR

Where this results in an out of tolerance figure the reading will be rejected.

The tolerance check applied in this test will be dependent upon the pulse value of the meter. Tolerance ranges are shown in Appendix B.

3.10 A reading which produces a negative consumption will only be accepted if followed by a consumption calculated from an estimate.

michele.downes 20/9/13 16:04

Deleted:

michele.downes 20/9/13 16:01

Formatted: Indent: Hanging: 1.25 cm

michele.downes 20/9/13 15:45

Deleted:

.

-

Deleted: 07

michele.downes 8/10/13 12:32

Emma Smith 15/10/13 15:28

michele.downes 20/9/13 15:21

Deleted: 20

Deleted: 2

Deleted: 0

michele.downes 8/10/13 12:32

Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

© all rights reserved

UNCVR

Daily Read Equipment - Class 1 DM Mandatory Supply **Points**

michele.downes 20/9/13 15:24

Deleted: Sites

The following tests will be performed by the Transporter.

Emma Smith 15/10/13 15:35

Deleted:

- 4.1 A completeness test to ensure that all the readings expected have been received.
- 4.2 An instrument configuration test i.e. to ensure that the convertor and the meter reading are received where a convertor is fitted. A report will be issued if any expected readings are not received or if an unsolicited reading is received.

Emma Smith 14/8/13 09:13

Deleted:

- For DM Supply Meter Points with Transporter Daily Read Equipment 4.3 installed, if 3 or more consecutive zero consumption readings are received a test will be performed to compare with the corresponding period in the previous year. If the consumption in the previous year was not zero then a report will be produced for investigation.
- 4.4 For DM Supply Meter Points with User Daily Read Equipment installed, zero consumption readings will be deemed to have been validated by the DMSP and will therefore be accepted.

michele.downes 20/9/13 15:27

Deleted: - assume above should be replaced with the new inner and outer tolerance checks

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Deleted: 07

michele.downes 8/10/13 12:32 Deleted: 20

michele.downes 8/10/13 12:32 Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

© all rights reserved UNCVR

<u>5</u> **Daily Read Equipment - Class 2 Sites**

The following tests will be performed by the Transporter.

- A completeness test to ensure that all the readings expected have been received. A report will be issued if any expected readings are not received. Where a convertor is fitted the read will be rejected if convertor readings are not supplied.
- For Class 2 Supply Meter Points with User Daily Read Equipment installed, zero consumption readings will be deemed to have been validated by the submitting user and will therefore be accepted.

michele.downes 20/9/13 15:46

Comment: Assume will be replaced by the new tolerance checks

michele.downes 20/9/13 15:46

Deleted: assume above will be replaced with the new inner/outer tolerance checks is there anything else that should be captured for Class 2??

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Emma Smith 15/10/13 15:24

Deleted: 07

michele.downes 8/10/13 12:32

Deleted: 20

michele.downes 8/10/13 12:32 Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

© all rights reserved UNCVR

Non Cyclic Meter Readings <u>6</u> michele.downes 20/9/13 16:05 Deleted: <u>6</u>,1 Non cyclic meter and convertor readings will be validated by the michele.downes 20/9/13 15:47 <u>Transporter</u> with the same rules as cyclic readings. Formatted: Font:(Default) Arial, 14 pt Emma Smith 14/8/13 09:33 Deleted: 5 6.2 Validation to ensure the read follows on from a previous actual reading. Emma Smith 14/8/13 09:33 Deleted: 5 The consumption tolerance limits set out in Appendix B will be used for all **6.3** michele.downes 20/9/13 15:43 non cyclic readings. Deleted: transporter Emma Smith 14/8/13 09:33 Deleted: 5 <u>6</u>,4 The RTC test as described in Appendix A will be applied by the Emma Smith 14/8/13 09:33 Transporter to non cyclic readings. Deleted: 5 michele.downes 20/9/13 15:44 Deleted: t Any previously received customer reading will be treated as an actual <u>6</u>,5 reading for tolerance checking purposes. Deleted: 5

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Deleted: 07

michele.downes 8/10/13 12:32

Deleted: 20

michele.downes 8/10/13 12:32

Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

© all rights reserved UNCVR

Calculated Gas Card Readings

- 7.1 The following refers to the calculation of a **Calculated Gas Card Reading** which (subject to compliance with section M<u>5.13</u>) can be used as an 'Opening Meter Reading' upon Supply Point Transfer.
- 7.2.1 Calculated Gas Card Readings will be subject to the same tests as detailed in Section 3, Cyclic Meter Readings.

michele.downes 20/9/13 15:47

Deleted: 6

michele.downes 20/9/13 15:47

Deleted: 6

Emma Smith 15/10/13 15:42

Deleted: 3.8

7.2 Formula

The Calculated Gas Card Reading shall be calculated in the same units as the Gas Card Reading from the Gas Card and will be calculated using the following formula:

$$(((c-b)/(b-a))*(y-x))+y$$

where:

a is the Accumulative Daily Value for first date in the Applicable Sequence.

b is the Accumulative Daily Value for last date in the Applicable Sequence.

c is the Accumulative Daily Value for the Supply Point Registration Date.

x is the First Reading in the Applicable Sequence.

y is the Last Reading in the Applicable Sequence.

- 7_2.2 No Calculated Gas Card Reading shall be calculated where **a** = **b** or where **x** = **y**.
- 7.2.3 For Metric calculation (M3) the Calculated Gas Card Reading shall be in the Range 00000.10 to 99999.90. [Note: The least significant digit is always zero].
- 7.2.4 For Imperial calculation (Cubic Feet) the Calculated Gas Card Reading shall be in the Range 0000.01 to 9999.99.
- The First Reading and Last Reading must be taken from a date within the six month period prior to the Supply Point Registration Date.

7.3 **Definitions**

7.3.1 Accumulative Daily Value

The value used to provide a seasonal adjustment factor within the formula. Values for the relevant date within the 'Applicable Sequence' are determined using the table in Appendix C.

7,3.2 Applicable Sequence

michele.downes 20/9/13 15:47

Deleted: 6

michele.downes 20/9/13 15:48

Deleted: 6

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Emma Smith 15/10/13 15:24

Deleted: 07

michele.downes 8/10/13 12:32

Deleted: 20

michele.downes 8/10/13 12:32

Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

© all rights reserved UNCVR

Joint Office of Gas Transporters Uniform Network Code - Validation Rules

The sequence of actual Gas Card Readings used to generate the Calculated Gas Card Reading (by execution of the formula).

7.3.3 Calculated Gas Card Reading

As defined in Uniform Network Code – Transportation Principal Document Section M1.4.3(h).

michele.downes 20/9/13 15:48

Deleted: 6

7.3.4 Gas Card Reading

As defined in Uniform Network Code – Transportation Principal Document Section M1.4.3(f).

michele.downes 20/9/13 15:48

Deleted: 6

7,3.5 First Reading

The first of the actual Gas Card Readings taken within the six month period prior to the Supply Point Registration Date.

michele.downes 20/9/13 15:48

Deleted: 6

7,3.6 Last Reading

The last of the second, third, fourth or fifth actual Gas Card Readings taken prior to the Supply Point Registration Date within the six month period prior to the Supply Point Registration Date.

michele.downes 20/9/13 15:48

Deleted: 6

7,3.7 Supply Point Registration Date

As defined in Uniform Network Code – Transportation Principal Document G1.1.5

michele.downes 20/9/13 15:48

Deleted: 6

Emma Smith 15/10/13 15:28

Deleted: 2

Deleted: 0

Deleted: 07

michele.downes 8/10/13 12:32 Deleted: 20

michele.downes 8/10/13 12:32 Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

© all rights reserved UNCVR

APPENDIX A - 'ROUND THE CLOCK' INDICATORS

REQUIREMENTS AND DEFINITIONS

 The term 'round the clock' will be used in a single context to denote that a meter or convertor has passed through all its zero's and will not necessarily imply that the meter or convertor has made a complete revolution of all its dials (i.e. more than 10,000 hundred cubic feet (hcf) on a four dial meter, 100,000 hcf on a five dial meter etc).

The indicator is to be used for all meters and convertors but in the remainder of the text the term meter will be used for ease of understanding.

2. This means that in the circumstance:

2.1 Present Reading 6000

Previous Reading 5000

If the volume passing through the meter is 1,000hcf then the RTC indicator will be 0.

If the volume passing through the meter is 1 1,000hcf (because the meter has made one complete revolution of all its dials) the RTC indicator will be 1. Here the meter has gone through the zero's once.

If the volume passing through the meter is 21,000hcf (because the meter has made two complete revolutions of all its dials) the RTC indicator will be 2. Here the meter has gone through its zeros twice.

2.2 Present Reading 0999

Previous Reading 9999

If the volume passing through the meter is 1,000hcf then the RTC indicator will be 1 as the meter has gone through the zero's once.

If the volume passing through the meter is 11,000hcf (because the meter has made one complete revolution of the dials) the RTC indicator will be 2 as the meter has gone through the zero's twice.

If the volume passing through the meter is 21,000hcf (because the meter has made two complete revolutions of all the dials) the RTC indicator will be 3 as the meter has gone through the zero's three times.

- 3. All RTC indicators of 2 or above will be reported for investigation .
- The test will also look for readings moving backwards because of a previous over-estimate.
- 4.1 Present Reading 9910 Actual

Previous Reading 0010 Estimate

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Emma Smith 15/10/13 15:24

Deleted: 07

michele.downes 8/10/13 12:32

Deleted: 20

michele.downes 8/10/13 12:32

Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

© all rights reserved U

UNCVR

If the present meter reading is lower than the previous meter reading this requires the meter to have passed backwards through the zero's the RTC indicator will be -1.

The previous estimate is clearly an over estimate if the test shows that a volume of -100hcf is more credible than a consumption of +9900hcf

Present Reading 5900 Actual Previous Reading 6000 Estimate 4.2

If the present meter reading is lower than the previous meter reading this does not require the meter to have passed backwards through the zero's the RTC indicator will be 0.

The previous estimate is clearly an over estimate if the test shows that a volume of -100hcf is more credible than a consumption of +9900hcf

- **NB:** A customer reading will be treated as an actual reading for the purpose of this test. The negative consumption indicator will only be used if the previous reading is an estimate.
- 5. The test to detect whether a meter has made more than one complete revolution of its dials will be applied only to 4 dial meters or where the previous reading is an estimate. For meters with 5 or more dials the reading will assumed to have gone forward unless the previous reading is an estimate.

Emma Smith 15/10/13 15:28 Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Deleted: 07

michele.downes 8/10/13 12:32

Deleted: 20 michele.downes 8/10/13 12:32 Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

© all rights reserved UNCVR

APPENDIX B - TOLERANCE RANGES,

A: Consumption Tolerance Ranges

Table 1 Daily Reads (Class 2 & 3) following an Actual read

Read validation tolerances on receipt of a daily read following an Actual Read. Read would be accepted if the consumption falls within the following tolerances.

Lower AQ band (kWh)	Upper AQ band (kWh)	Override Read Tolerance (can override with 'flag')	'Market Breaker' Read Tolerance (can not override with 'flag')
<u>0</u>	<u>73,200</u>	<u>0 - 73,200 kWh</u>	<u>0 – 700% of SOQ</u>
<u>73,201</u>	732,000	10% - 100% of SOQ	<u>0 - 650% of SOQ</u>
732,001	2,196,000	10% - 100% of SOQ	<u>0 - 600% of SOQ</u>
<u>2,196,001</u>	29,300,000	10% - 100% of SOQ	<u>0 - 550% of SOQ</u>
29,300,001	58,600,000	10% - 100% of SOQ	<u>0 - 500% of SOQ</u>
<u>58,600,001</u>	and above	10% - 100% of SOQ	<u>0 - 450% of SOQ</u>

Table 2 Validation on Daily Reads (Class 2 & 3) following an Estimate

Read validation tolerances on receipt of a daily read following an Estimated Read. Read would be accepted if the consumption falls within the following tolerances.

Lower AQ band (kWh)	Upper AQ band (kWh)	Override Read Tolerance (can override with 'flag)	'Market Breaker' Read Tolerance (can not override with 'flag')
<u>0</u>	73,200	No greater than + or – 73,200 kWh	+ or - 700% of SOQ
<u>73,201</u>	732,000	+ or - 100% of SOQ	+ or - 650% of SOQ
732,001	2,196,000	+ or - 100% of SOQ	+ or - 600% of SOQ
2,196,001	29,300,000	+ or - 100% of SOQ	+ or - 550% of SOQ
29,300,001	58,600,000	+ or - 100% of SOQ	+ or - 500% of SOQ
58,600,001	and above	+ or - 100% of SOQ	+ or - 450% of SOQ

Table 3: Read validation on a Periodic Read (Class 4)

Read validation tolerances on receipt of a periodic read. Read would be accepted if the consumption falls within the following tolerances.

Lower AQ band (kWh)	Upper AQ band (kWh)	Override Read Tolerance (can override with 'flag')	'Market Breaker' Read Tolerance (can not override with 'flag')
0	73,200	20% - 300% of AQ/365 x no. of days	0 – 700% of AQ/365 x no. of days
<u>73,201</u>	732,000	20% - 250% of AQ/365 x no. of days	[0 - 650% of AQ/365 x no. of days

michele.downes 20/9/13 16:08

michele.downes 20/9/13 15:28

Deleted: replace with new table Emma Smith 14/8/13 09:19

michele.downes 20/9/13 16:07

Formatted: Font:Bold
michele.downes 20/9/13 16:07
Formatted: Font:Bold

Deleted:

Formatted: Font:Bold

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Emma Smith 15/10/13 15:24

Deleted: 07

michele.downes 8/10/13 12:32 **Deleted:** 20

michele.downes 8/10/13 12:32 **Deleted:** 01

michele.downes 20/9/13 15:21

Deleted: 1

Version 2.<u>3,15/10/2013</u>

© all rights reserved

UNCVR

Joint Office of Gas Transporters Uniform Network Code – Validation Rules

732,001	2,196,000	20% - 200% of AQ/365 x no. of days	<u>0 - 600% of AQ/365 x no. of</u> <u>days</u>
<u>2,196,001</u>	29,300,000	20% - 150% of AQ/365 x no. of days	<u>0 - 550% of AQ/365 x no. of</u> <u>days</u>
29,300,001	58,600,000	20% - 100% of AQ/365 x no. of days	<u>0 - 500% of AQ/365 x no. of</u> <u>days</u>
58,600,001	and above	20% - 100% of AQ/365 x no. of days	0 - 450% of AQ/365 x no. of days

Note: The Market Breaker Tolerances would be greater or less than the Override Read Tolerances

michele.downes 20/9/13 16:07

Deleted: Table 1: Inner Tolerance Range

Estimated Consumption cf

Emma Smith 15/10/13 15:28 **Deleted:** 2

michele.downes 20/9/13 15:21

Deleted: 0

Emma Smith 15/10/13 15:24

Deleted: 07

michele.downes 8/10/13 12:32

Deleted: 20

michele.downes 8/10/13 12:32

Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

© all rights reserved

UNCVR

APPENDIX C - CALCULATED GAS CARD READINGS

The following table is used to determine the 'Accumulative Daily Value' for application within the formula

Table 4:

© all rights reserved

Month	Date	Seasonal Factor	Seasonal Factor /	Accumulative Daily Value
			100	
January	01/01/04	13.80	0.138	0.138 = 0.138 + 0
	02/01/04		0.138	0.276 = 0.138 + 0.138
	03/01/04		0.138	0.414 = 0.276 + 0.138
			"	ω
February	01/02/04	13.60	0.136	4.414 = 4.278 + 0.136
	02/02/04		0.136	4.55 = 4.414 + 0.136
	03/02/04		0.136	4.686 = 4.55 + 0.136
			u	и
March	01/03/04	12.20	0.122	8.344 = 8.222 + 0.122
	02/03/04		0.122	8.466 = 8.344 + 0.122
	03/03/04		0.122	8.588 = 8.466 + 0.122
			u	и
April	01/04/04	09.80	0.098	12.102
May	01/05/04	07.10	0.071	15.015
June	01/06/04	04.20	0.042	17.187
July	01/07/04	02.40	0.024	18.429
August	01/08/04	02.40	0.024	19.173
September	01/09/04	04.20	0.042	19.935
October	01/10/04	07.30	0.073	21.226
November	01/11/04	10.30	0.103	23.519
December	01/12/04	12.70	0.127	26.633
January	01/01/05	13.80	0.138	30.581
January	01/01/06	13.80	0.138	60.888
January	01/01/07	13.80	0.138	91.195
January	01/01/08	13.80	0.138	121.502
January	01/01/09	13.80	0.138	151.945
January	01/01/10	13.80	0.138	182.252
January	01/01/11	13.80	0.138	212.559
January	01/01/12	13.80	0.138	242.866
January	01/01/13	13.80	0.138	273.309
January	01/01/14	13.80	0.138	303.616
January	01/01/15	13.80	0.138	333.923
January	01/01/16	13.80	0.138	364.230
January	01/01/17	13.80	0.138	394.673
January	01/01/18	13.80	0.138	424.980
January	01/01/19	13.80	0.138	455.287
January	01/01/20	13.80	0.138	485.594
January	01/01/21	13.80	0.138	516.037
January	01/01/22	13.80	0.138	546.344
January	01/01/23	13.80	0.138	576.651
January	01/01/24	13.80	0.138	606.958

Deleted:If the Meter Pulse value is unknown the default test will be on 1000cf/Pulse tolerances.

Emma Smith 15/10/13 15:28

Deleted: 2

michele.downes 20/9/13 15:21

Deleted: 0

Deleted: 07

michele.downes 8/10/13 12:32 Deleted: 20

michele.downes 8/10/13 12:32 Deleted: 01

michele.downes 20/9/13 15:21

Deleted: 1

UNCVR Version 2.3.15/10/2013