The Voice of the Networks



# GDN/PM/GT2

MANAGEMENT PROCEDURE FOR;

# **REQUESTING A GAS TRANSPORTER TO:**

- AUTHORISE THE SETTING AND SEALING OF REGULATORS AND ASSOCIATED SAFETY DEVICES.
- AUTHORISE THE INSTALLATION OF A METER BY-PASS
- APPROVE A METER HOUSING DESIGN.

# CONTENTS.

CONTENTS	2
FOREWORD	3
BRIEF HISTORY	3
KEY CHANGES	3
DISCLAIMER	
Mandatory and non-mandatory requirements	
Introduction	
Scope	
Obtaining an Authorisation to set and seal a meter regulator.	
Overview of Authorisation process	
Identifying the correct form to use.	
Submitting a request for Authorisation to set and seal a Meter Regulator	
Reviewing a Request for Authorisation to set and seal a Meter Regulator	
Authorisation to set and seal a Meter Regulator and any associated pressure control and protection	
devices	
Maintaining an Authorisation	
Removal of Authorisation	
Administration	10
Requesting Authorisation to Install a Meter By-pass	11
Provision of a meter by-pass.	
GT Authorisation.	
Removal of existing meter by-pass.	11
Sealing of by-pass valves and equipment	11
Approval of Gas Supply Meter Housings.	
General requirements:	11
Criteria for approval.	
Information required for approval.	12
APPENDIX A: Legislation and References	13
APPENDIX B: Definitions	
APPENDIX C: Request for Authorisation to set & seal regulators forms	17
APPENDIX D: GT check lists for reviewing a Request for Authorisation.	31
APPENDIX E: GT meter installation inspections.	37
APPENDIX F Bypass Authorisation request form	
APPENDIX G: Form for requesting meter housing / accommodation approval	
APPENDIX G2: Supporting Information required for meter housing approval.	41
APPENDIX H: Letters of Authorisation / rejection.	
APPENDIX I: Pressure control arrangements	
APPENDIX J: Addresses & WEB SITE links	54

Table 1 Categories of meter installation within the scope of the procedure	5
Table 2: The forms to be used by the applicant to request an Authorisation to set, seal and break a	
regulator seal	7
Table 3: Forms and Letters used by the GT to review the request	7
Table 4: Network pressure tiers.	52
Table 5. Guidance on Meter Installation Categories	53

## FOREWORD

The original procedures used by the Gas Transporters (GT) have now been superseded by this document. As a result there is no brief history of the management procedures from an individual GT.

This generic Management Procedure was approved by a collaboration of Gas Transporters on 18<sup>th</sup> February 2014 for use by managers, engineers and supervisors. This will give a consistent framework and approach for those who will use this document.

This document will be revised, when necessary, by the issue of new editions. Users should ensure that they are in possession of the latest edition by referring to the Energy Network Association website.

Compliance with this document does not confer immunity from prosecution for breach of statutory or other legal obligations.

#### **BRIEF HISTORY**

Version 1.0, published following amalgamation of 4	May 2013	GDN/PM/GT2
DN versions. DN versions discontinued.		
Version 1.1, Revisions agreed but not published.	September 2013	
Version 1.2, Revisions agreed and published	January 2014	
Version 1.3 Revisions agreed and Published	August 2015	
	_	

#### **KEY CHANGES**

(Identify the changes from the previous version of this document)

Section	Amendments			
Obtaining Authorisation	Notification of non-standard meter exchanges Use of FM176 form			
Appendix C	Minor changes to forms.			

#### DISCLAIMER

This document is provided for use by GTs and such of its contractors as are obliged by the terms and conditions of their contracts to comply with this document. Where this document is used by any other party it is the responsibility of that party to ensure that this document is correctly applied.

#### Mandatory and non-mandatory requirements

In this document:

- **Shall:** Prescribes a procedure which it is intended will be complied with in full, without deviation.
- **Should:** Prescribes a procedure which it is intended will be complied with unless, after prior consideration, deviation is considered to be acceptable.

#### Introduction

Legislation, industry codes and standards describe how certain meter related activities require GT Authorisation and / or approval (see appendix A).

The Gas Safety (Management) Regulations 1996 place a duty on a GT to ensure that gas is at a suitable pressure to ensure the safe operation of any appliance that a consumer could reasonably expect to operate.

The Gas Safety (Installation and Use) Regulations 1998 requires that the person who installs or adjusts a regulator shall ensure that it is adequately sealed. This seal is to prevent the setting from being adjusted or interfered with. No person except the GT or a person authorised to act on his behalf shall break the seal applied to the regulator.

The HSE have considered that the Gas Safety (Management) Regulations 1996 should be taken as meaning that a GT is deemed to have 'control of the meter regulator'. This should ensure the integrity of the system downstream of the meter regulator, and as far as reasonably practical, ensure that the downstream system is supplied with a satisfactory pressure to ensure the safe combustion of gas at a gas appliance.

The Unified Network Code requires that following approval by a Gas Shipper, the provision and use of a meter by-pass shall be approved by the GT.

The Gas Act 1986 (As amended) requires that where a meter is to be installed in a meter house, the type and construction of the meter house shall be approved by the GT. Failure to obtain approval could result in the GT refusing to connect, or as the case maybe, disconnect the gas supply to the consumer's premises.

Where a meter installation is or is intended to be connected to a network operated by a GT, 'Authorisation' applies to any activity associated with the;

- Initial setting of a regulator, sealing or breaking a seal and adjustment of a regulator and any associated pressure control or protection devices,
- Installation of a meter by-pass.
- Design of meter housing.

This procedure shall be used by a Meter Asset Manager (MAM) to request an Authorisation.

The GT shall review requests and issue a 'Letter of Authorisation' or 'Notification of failure to obtain an Authorisation'.

The review will be limited to ensuring that the:

- Design of the gas supply meter installation is compatible with the operational pressures that may occur on the network to which the meter installation is to be connected,
- Appropriate pressure control and protection device(s) will be used,
- Pressure control and protection device(s) will be set at specified values,
- Gas supply meter installation will not absorb excessive pressure so as to affect the safe operation of any appliance a consumer may reasonably be expected to operate,
- Provision of a by-pass is appropriate and has been approved by a Gas Supplier.
- The meter housing is of an acceptable design.

The review will specifically exclude any validation that a meter satisfies the obligations under the Gas Act 1986 (as amended) Schedule 2B with respect to the meter being of a type appropriate for registering the quantity of gas supplied and any other statutory requirements, recommendations or good practices associated with a meter installation in a premises.

Electronic copies of this procedure can be obtained from the Energy Network Association and GT's web site. (See Appendix J).

## Scope

This procedure applies to gas supply meter installations as described in Table 1 below that are, or are intended to be connected to a network operated by a GT for the transportation of Second Family Gas.

This procedure describes how to obtain GT Authorisation for;

- Setting and sealing meter regulators (Section 3)
- Setting and sealing any associated pressure control and protection devices (Section 3)
- Installing a meter by-pass. (Section 4)
- Approval of meter housing design. (Section 5)

It also describes how the GT verifies that the conditions associated with an Authorisation are satisfied.

#### TABLE 1 CATEGORIES OF METER INSTALLATION WITHIN THE SCOPE OF THE PROCEDURE

Work Category	Installation Details	Installation Description
Category 1 & COP 1a	Qmax <u>&lt;</u> 6 m <sup>3</sup> h MOP <u>&lt;</u> 75 mbar Standard Installation	Domestic Meter Installations supplied at Low Pressure and installed in accordance with BS 6400 - 1
Category 2 & COP 1c	Qmax <u>&lt;</u> 6 m³ h 75 mbar < MOP <u>&lt;</u> 2 bar Standard Installation	Domestic Meter Installations supplied at Medium Pressure and installed in accordance with BS 6400 - 2
Category 3a & COP 1b	6 m <sup>3</sup> h < Qmax $\leq$ 40 m <sup>3</sup> h MOP $\leq$ 75 mbar Standard Installation	Domestic Meter Installations up to U40 supplied at Low Pressure and installed in accordance with IGEM/GM/6
Category 3b & COP 1b	6m³ h < Qmax <u>&lt;</u> 1076m³ h MOP <u>&lt;</u> 75 mbar Standard Installation	Industrial and Commercial Meter Installations supplied at Low Pressure and installed in accordance with IGEM/GM/6
Category 4a & COP 1c	Qmax > $6m^3 h$ 75mbar < MOP $\leq$ 38 bar Non standard Installation	Industrial and Commercial Meter Installations supplied at pressures up to and including 38 bar, with a Metering Pressure of 21 mbar and installed in accordance with IGE/GM/8
Category 4b & COP 1c	Qmax > 6m <sup>3</sup> h 75mbar < MOP <u>&lt;</u> 100 bar Non standard Installation	Industrial and Commercial Meter Installations supplied at pressures between 16 bar and 38 bar and installed in accordance with IGE/GM/8 or GM4 for installation up to 100 bar and where the metering pressure is greater than 21 mbar.


Note 1: For supply points covered by a Gas Network Exit Agreement there may be additional requirements associated with the provision of the supply meter installation e.g. it may not be necessary for the applicant to be a Registered MAM.

Note 2: Where the meter installation is to supply a gas engine, compressor or any other apparatus which requires the use of anti-fluctuation devices or valves to protect the gas network, this shall be included in the GT2 request.

### Obtaining an Authorisation to set and seal a meter regulator.

#### **Overview of Authorisation process**

Figure 1: How to obtain an Authorisation.



Authorisations extend to;

- new meter installation work,
- meter exchange
- modifications to meter installations.

Note 1: "modifications" includes any change to the set points that will take the installation out of the regime specified on the warrant.

Work relating to the authorisation should not commence, until authorisation is obtained and the meter installation shall not be put into service until authorisation is obtained.

The above process relies on an exchange of correspondence between the applicant and the GT using the forms identified in Table 2 and Table 3 and shown in Appendix C and Appendix H.

Note: Where an application is made for a Cat 4 installation, the network operational pressure limits for the site should be obtained from the GT using procedure GDN/PM/GT/1.

#### Identifying the correct form to use.

# TABLE 2: THE FORMS TO BE USED BY THE APPLICANT TO REQUEST AN AUTHORISATION TO SET, SEAL AND BREAK A REGULATOR SEAL.

(See Appendix C)

1	Category	Meter Capacity	Appropriate metering pressure	Appropriate for connection to	Request for Authorisation' Form	Type of Authorisation
1	Low pressure, domestic size meter installations	≤ 6 m³/h	21 mbar	Low pressure networks operating at standard pressures.	C1	Generic
2	Medium pressure, domestic size meter installations	≤ 6 m³/h	21 mbar	Medium pressure networks operating at standard pressures.	C2	Generic.
3A	Low pressure, standard, domestic size meter installations	≤ 40 m³/h	21 mbar	Low pressure networks operating at standard pressures.	C3A	Generic.
3B	Low pressure, standard, industrial and commercial size meter installations	≤ 1076 m <sup>3/</sup> h	21 mbar	Low pressure networks operating at standard pressures.	C3B	Generic.
4A	Low pressure non standard, or higher pressure industrial and commercial size meter installations	As stated on the 'Request for Authorisation'	21 mbar	Networks operating at standard pressures as stated on the 'Request for Authorisation'.	C4A	Specific applicable only to the meter being installed
4B	Low pressure non standard, or higher pressure industrial and commercial size meter installations	As stated on the 'Request for Authorisation'.	As stated on the 'Request for Authorisation'.	Networks operating at standard pressures or at enhanced pressure under a gas supply ancillary agreement as stated on the 'Request for Authorisation'.	C4B	Specific applicable only to the meter being installed

#### TABLE 3: FORMS AND LETTERS USED BY THE GT TO REVIEW THE REQUEST

(See Appendices D & H)

Request for Authorisation	GT Review of Request Form	GT Letter of Authorisation	GT Authorisation Failure Letter
C1	D1	E1	
C2	D2	E2	
C3A	D3A	E3A	F
C3B	D3B	E3B	
C4A	D4A	E4A	
C4B	D4B	E4B	

Note 1: Subject to a satisfactory review, a 'Letter of Authorisation' will be issued which details the conditions of a particular Authorisation. This will be either generic or specific, dependant upon the category of the installation and the details stated in the request.

Note 2: A generic Authorisation is applicable to all meter installations within the defined category that fit the description given on the 'Request for Authorisation'.

Note 3: A specific Authorisation is applicable only to a single meter installation.

#### Submitting a request for Authorisation to set and seal a Meter Regulator.

The appropriate 'Request for Authorisation' form for the particular category of meter installation shall be used. (See Appendix C)

Consider the following prior to completing an application:

- Determine the Network Pressure. See Table 4 in Appendix I.
- If there is doubt about the pressure tier or where the supply capacity is to be increased a GT1 application should have been completed. The response from the GT1 request, shall be appended to the GT2 application when it is submitted.
- Where it is a new connection the FM176 form can be submitted with the GT2 application along with the service design and quotation reference number.
- What are the proposed or existing, capacity and characteristics of the appliances that will be supplied with gas?
- What is the required metering pressure?
- Are the gas supply arrangements for the meter installation appropriate?
- Is the design of the proposed meter installation compatible with the operational pressures of the network to which it will be connected?
- Has permission been requested for a by-pass?
- What pressure control and protection arrangements will be employed?
- Are the settings for the meter regulator and any associated pressure control and protection device(s) appropriate? See Appendix I.
- Is the meter installation un-regulated and is an exemption certificate under Regulation 40 of the Gas Safety (Installation and Use) Regulations 1998 required?
- Is the installation pipework, gas fittings and gas appliance(s) suitable for the pressures that may occur at the outlet of the meter installation under all circumstances?
- Is the organisation submitting the request a registered MAM or is the supply point subject to a Network Exit Agreement?
- Is the organisation undertaking the work an OAMI or will an OAMI be required to set and adjust the meter regulator and any associated pressure control and protection device(s)?
- Does the proposed meter installer and OAMI have the appropriate accreditations to undertake this category of work?
- Is the meter house / accommodation of a type and construction approved by the GT?

If the requirements above are not complied with, the GT may refuse to connect or, as the case may be, decide to disconnect the gas supply at the consumer's premises.

Where the installation is designed for consumer specific outlet pressures, e.g. When "Standard appliances" are not used, a copy of the letter from the consumer advising the operational limits of the downstream system shall be submitted with the application.

Where the meter installation is to be installed prior to there being any knowledge of the downstream installation pipework or gas appliance(s) then the applicant shall assume that only standard appliances will subsequently be connected.

A GT will only authorise an OAMI to break a seal, set and seal the meter regulator and any associated pressure control and protection device(s). If the applicant is not an OAMI, or the applicant does not wish to break a seal, set and adjust the meter regulator and any associated pressure control and protection device(s), then the applicant will need to contact an OAMI to undertake this activity. The OAMI who will be undertaking this activity shall sign the relevant section of the appropriate 'Request for Authorisation' form.

#### Notification of Non-Standard meter exchanges in emergency situations.

A GT2 application is not required if a MAM carries out a meter exchange where it is only the meter that is replaced e.g. where the meter is faulty and the work is carried out by an OAMI that has previously been subject to a GT2 approval for the MAM on that Network. Where there are any material changes to the installation including hardware or settings or breaking of seals or there is a change to the MAM and/or OAMI, a new application is required but this can be submitted within 5 days of completion of the work. The 5 days are only applicable where it has been deemed that these works are an emergency in that there is a potential threat to safety or a supply failure. Any other meter exchanges must have a GT2 submission prior to any works being undertaken."

#### Reviewing a Request for Authorisation to set and seal a Meter Regulator.

Following receipt of a 'Request for Authorisation' the GT shall review the request and ensure that the following general criteria are satisfied:

- the arrangement of the meter regulator, associated pressure control and protection device(s) meet industry accepted practice and standards
- the settings requested for the meter regulator and any associated pressure control and protection device(s) are consistent with the range of pressures that both the appliance(s) and installation pipework are designed to operate; and
- the meter regulator should lock up at zero flow and in conjunction with any associated pressure control and protection device(s) limit the downstream pressure to an acceptable level when gas is supplied from the Network at the maximum operating pressure and the design maximum incidental pressure; and
- the proposed control and protection system and settings are consistent with acceptable arrangements and settings detailed in Appendix I; and
- other criteria detailed on the review forms in Appendix D.

If the 'Request for Authorisation' is incomplete or is not consistent with the criteria above, the request shall be rejected and the Failure 'Notification Letter' (Letter F), shall be sent to the applicant.

The GT's Competent Person shall undertake an appraisal of the statements in the 'Request for Authorisation'.

# Authorisation to set and seal a Meter Regulator and any associated pressure control and protection devices.

Subject to a satisfactory review the GT shall issue a 'Letter of Authorisation' to the applicant using one of the letters contained in Appendix H, (Letters E1, E2, E3A, E3B, E4A, E4B.)

The Authorisation shall be subject to the following conditions:

- The organisation managing the meter installation is a Registered MAM, and
- The organisation undertaking the work is an OAMI, and
- The person undertaking the activity is competent and where appropriate accredited to do so, and
- The meter installation and housing are designed and will be installed in accordance with relevant industry standards and
- The meter regulator and any associated pressure control and protection device(s) are set to the values stated in the 'Letter of Authorisation', and
- The meter regulator and any associated pressure control and protection device(s) settings are clearly labelled on the installation, and
- The meter regulator and any associated pressure control and protection device(s) are subsequently sealed, to prevent unauthorised adjustment, with a seal marked with the OAMI registration number, and

• Any other conditions specified in the 'Letter of Authorisation'.

#### Maintaining an Authorisation

In order to ensure compliance with the undertakings made by the applicant in the 'Request for Authorisation' the GT reserves the right to inspect the meter installation whether it is a new installation, has been modified, exchanged or where the pressure settings have been set outside the original warrant.

All Cat 4 meter installations shall be inspected. However, where evidence proves a MAM's continued compliance with these procedures, the number of inspections carried out can be reduced in line with the perceived risk.

In order to facilitate the inspection regime, the MAM shall notify the GT via email (see appendix J) when a Category 4 installation is complete. For all other installations the GT should be notified via a system update e.g. Xoserve report. Inspections should be carried out within 12 months of the GT being notified and the number of inspections should be determined by the GT based on a number of risk factors including;

- The number of installations carried out by a MAM;
- Evidence of non-compliance with this procedure by the MAM / OAMI;
- Evidence of other non-compliance issues e.g. Gas escapes, RIDDOR etc.

Inspections shall be carried out by a Competent Person appointed by the GT and to ensure a consistent standard of inspection, mandatory requirements have been identified which shall form the basis for inspection. (See Appendix E).

Note; the Competent Person will deal with Unsafe Situations identified on site by taking the appropriate action.

The GT shall review inspections to determine compliance with the statements in the 'Request for Authorisation' and the 'Letter of Authorisation' and where appropriate the requirements of IGE/GL/5 edition 2.

#### **Removal of Authorisation**

The GT may withdraw an Authorisation in the event that:

- Gas Safe Register or any other body remove the registration or certificate of competence required by a meter installer to lawfully act as such;
- OFGEM remove the MAM / OAMI registration or certificate of compliance with the MAMCoP;
- The GT has material evidence that a meter installer is not operating in a manner consistent with the 'Request for Authorisation' or the 'Letter of Authorisation'.

Before the withdrawal of any Authorisation, the GT shall notify the MAM of their intention so as to provide an opportunity for the meter installer to submit further information to the MAM as to why the Authorisation should not be withdrawn.

Any evidence of non-compliance may be passed to the MAMCoP Board, a Nationally Accredited Certification Body, Gas Safe Register or the HSE in accordance with any requirements in force at the time or at the GT's discretion.

#### Administration

The GT shall ensure that adequate records are maintained of:-

- Requests for Authorisation (including any supporting information submitted).
- Correspondence between an applicant(s) and GT.
- Check lists / Inspection forms etc. used to review a 'Request for Authorisation'.
- Letters of Authorisation / failure to obtain Authorisation.

Such records shall be retrievable in order to facilitate management of the procedure.

## Requesting Authorisation to Install a Meter By-pass

#### Provision of a meter by-pass.

A meter by-pass shall be provided only where the Gas Supplier has deemed it necessary in order to avoid the risk of personal injury or death or damage to property (including prejudice to animal welfare) arising from a fault on the meter or metering equipment.

A by-pass should only be considered for the following types of premises:

- Hospitals or hospice
- Institutionalised accommodation (e.g. homes for the elderly, schools, and prisons)
- Large or complex plant supporting continuous processes (e.g. agricultural, baking processes)

And at meter installations connected to:

- Exceptionally complex pipework and gas consuming plant
- Multi-occupied premises (e.g. a single meter installation serving a block of flats).

#### GT Authorisation.

Where the Gas Supplier has identified the need for a by-pass, the MAM shall:

- Submit a written request to the GT including justification for the by-pass by using the form in Appendix F).
- Not install the by-pass until the approved form has been returned.

#### Removal of existing meter by-pass.

A meter by-pass shall only be removed at the GT or the Gas Act owner's discretion. Consideration should be given to removing the by-pass under the following conditions:

- It is suspected that the by-pass has been misused in any way
- The by-pass has been installed without the GT's Authorisation
- Where circumstances have changed and no longer meet the criteria for provision of a by-pass.

#### Sealing of by-pass valves and equipment.

In order to minimise the opportunity for gas to flow undetected through the by-pass and to protect the system and consumers, the MAM shall ensure it is sealed with the relevant OAMI seal and in accordance with IGE/GM/8 such that the operation of the by-pass valve is evident.

#### Approval of Gas Supply Meter Housings.

#### **General requirements:**

The Gas Act requires a consumer to obtain approval from the GT for certain types of housing and relevant industry standards require that any meter installation location shall be agreed with the GT. When a meter is not to be installed within the premises or a pre-fabricated enclosure manufactured to a relevant standard or specification, GT approval is required for the type and construction of the meter housing where:

- a) it is to be installed in a separate meter house or other accommodation and;
- b) gas has not previously been conveyed by the GT to the consumer's premises and;
- c) a new or substituted pipe is to be laid between the GT's main and the meter or;
- d) the meter is to be installed in a different position.

The GT has the right to refuse to connect or, as the case may be, disconnect the consumers premises, where it has reason to believe that the housing / location is not appropriate, particularly with respect to safety or where it does not comply with relevant legislation.

#### Criteria for approval.

Approval shall be granted only when the housing / location meets the following criteria:

- Complies with relevant legislation and industry standards;
- Is located as close as practicable to the site boundary nearest to the gas main;
- Does not create an unsafe environment;
- Has a total effective ventilation area that is sufficient to ensure that any hazardous area zone within the housing is no worse than;
  - Domestic = Zone 2
    - Industrial and commercial = Zone 1
- Has an explosion relief, if required,
- Has sufficient access for the Consumer and the ESP to operate the ECV;
- Enables the GT to have adequate access to undertake its' obligations under GS(M)R and GS(I&U)R;
- Suitable access provided to facilitate the installation and subsequent inspection, meter reading and maintenance activities
- The site is freely available to authorised personnel at all reasonable times;
- Provides adequate protection against vandalism and unauthorised access;
- The GT is informed of any special precautions that may be required before entering the meter housing / accommodation.

Note: GT 'approval' does not confer or imply granting of planning permission. The obtaining of planning permission, where needed, is the responsibility of the consumer/housing designer. Neither does GT 'approval' imply the durability of any housing, or meter installation is appropriate for use.

#### Information required for approval.

To obtain approval for a meter housing / accommodation the applicant shall complete the form in Appendix G and submit it to the GT with the required supporting information as detailed in Appendix G2:

On receipt of a completed form and relevant information the GT shall assess the housing/accommodation for compliance with the criteria specified in clause 5.2.

Approval / rejection shall be given in the form of a letter as detailed in Appendix H. (Letter G1 / G2)

## **APPENDIX A: Legislation and References**

#### A.1 GAS SAFETY (MANAGEMENT) REGULATIONS 1996

#### A.1.1 Regulation 8

Regulation 8 schedules 3 part 1 paragraph 3 places the following duty on the gas transporter: "The gas shall be at a suitable pressure to ensure the safe operation of any gas appliance which a consumer could reasonably be expected to operate"

#### A.2 GAS SAFETY (INSTALLATION AND USE) REGULATIONS 1998

The Regulations place duties on persons undertaking work or using gas systems within the context of a business or domestic environment.

#### A.2.3 Regulation 14 (1)

"No person shall install a primary meter or by-pass used in connection with a primary meter unless:

- a) there is a regulator controlling the pressure of gas supplied through the meter or the by-pass, as the case may be, which provides adequate automatic means for preventing the gas fittings connected to the downstream side of the regulator from being subjected to a pressure greater than that for which they were designed
- b) where the normal pressure of the gas is 75 mbar or more at the inlet to the regulator, there are also adequate automatic means for preventing, in case the regulator should fail, those fittings from being subject to such a greater pressure; and
- c) where the regulator contains a relief valve or liquid seal, such valve or seal is connected to a vent pipe of adequate size and so installed that it is capable of venting safely."

#### A.2.4 Regulation 14 (5)

"Where a person installs a regulator for controlling the pressure of gas through a primary meter, a meter bypass used in connection with a primary meter or from a gas storage vessel, or installs a gas appliance itself fitted with a regulator for controlling the pressure of gas to that appliance, he shall immediately thereafter ensure, in either case, that the regulator is adequately sealed so as to prevent its setting from being interfered with without breaking of the seal.A.2.5 Regulation 14 (6)

"In relation to gas from:

- a) a distribution main, no person except the transporter or a person authorised to act on his behalf;
- b) a gas storage vessel, no person except the supplier or a person authorised to act on his behalf;

shall break a seal applied under paragraph (5) above other than a seal applied to a regulator for controlling the pressure of gas to the appliance to which that regulator is fitted."

#### A.2.6 Regulation 14 (7)

"A person who breaks a seal applied under paragraph (5) shall apply as soon as is practical a new seal which is adequate to prevent the setting of the regulator from being interfered with without breaking such seal."

#### A.3. Gas Safety (Rights Of Entry) Regulations 1996

These regulations give GT's extensive powers to enter premises for the purposes of inspection of gas fittings etc.

### A.3.1 Regulation 5

"Any officer authorised by the relevant authority may, on production of some duly authenticated document showing his authority

- a) enter any premise in which there is a service pipe connected with a gas main for the purpose of inspecting any gas fitting on the premises, any flue or means of ventilation used in connection with such gas fitting, or part of the gas system on the premises, that is to say, any service pipe or other apparatus (not being a gas fitting) which is on the premises and is used for the conveyance or supply of gas or is connected with a gas main,
- b) where he so enters any such premises, examine or apply any test to any such object as is mentioned in paragraph (a) and (where the object is a gas fitting) verify what supply of air is available for it, and
- c) where in his opinion it is necessary to so do for the purpose of averting danger to life or property, and notwithstanding any contract previously existing, disconnect and seal off any gas fitting or any part of the gas system on the premises or disconnect the premises or, if the premises are not connected, signify the refusal of the relevant authority to convey gas or, as the case may be, allow gas to be conveyed to the premises."

#### A 4 Gas Act 1986 (as amended 1995), Schedule 2B

5 (2) Subject to sub-paragraph (3) below, the meter shall be installed as near as practicable to the public gas transporter's main, but within a building comprised in the premises.5 (3) The meter may be installed otherwise than within a building comprised in the premises if it is installed either:

- a) in accommodation of a type and construction approved by the public gas transporter by an approval given in relation to premises generally, or to any class or description; or
- b) in a separate meter house or other accommodation outside a building comprised in the premises which is approved by the public gas transporter in the case of those particular premises.

5 (4) If the requirement of the above paragraph are not complied with, the public gas transporter may refuse to connect or, as the case may be, disconnect the consumer's premises."

#### A 5 Reference to standards and other procedures

**BS6400-1:** Specification for installation of domestic-sized gas meters maximum rated capacity not exceeding 6 m<sup>3</sup>/h (2<sup>nd</sup> and 3<sup>rd</sup> family gases) - Part 1: Low pressure (2<sup>nd</sup> family gases).

**BS6400-2:** Specification for installation of domestic-sized gas meters maximum rated capacity not exceeding 6 m<sup>3</sup>/h (2<sup>nd</sup> and 3<sup>rd</sup> family gases) - Part 2: Medium pressure (2<sup>nd</sup> family gases).

**IGE/G/1:** Definitions for the end of a network, a meter installation and installation pipework.

IGE/GM/4 Flow metering practice for pressures between 38 and 250 bar

**IGEM/GM/6:** Specifications for low-pressure diaphragm and rotary displacement meter installations with badged meter capacities exceeding 6m<sup>3</sup>/h but not exceeding 1076 m<sup>3</sup>/h.

**IGE/GM/8:** Non-domestic meter installations. Flow rate exceeding 6 m3 h and inlet pressure not exceeding 38 bar.

**IGE/GL/5 Ed 2:** Procedure for managing networks, modifications and repairs.

**Ofgas COP/1a:** Code of practice for low-pressure diaphragm and electronic meter installations with badged meter capacities not exceeding 6 m<sup>3</sup>/hr.

**Ofgas COP/1b:** Code of practice for low-pressure diaphragm and rotary displacement meter installations with badged meter capacities exceeding 6 m<sup>3</sup>/hr but not exceeding 1076 m<sup>3</sup>/hr.

**Ofgas COP/1c:** Code of practice for all high pressure and other low-pressure meter installations not covered by COP/1a or COP/1b.

GDN/PM/GT/1: Procedure for requesting gas service pipe pressure and capacity information from GT's.

#### **APPENDIX B: Definitions**

For the purposes of this Procedure the following definitions apply:

**Applicant:** The organisation or person who is to take full responsibility for the installation being undertaken by their organisation.(includes breaking a seal, setting and sealing of the meter regulator and any associated pressure control and protection device(s) and installing a by-pass).

**Approved Code of Practice:** Practical guidance produced by HSE to assist compliance with regulations.

**Competent Person:** An individual who holds an appropriate and valid certificate of competence under the Nationally Accredited Certification Scheme or an Approved Code of Practice.

**Consumer ("c" subscript):** The position on the gas system where the pressure reading is taken where this is downstream of the meter installation.

**Design Maximum Incidental Pressure (DMIP):** The maximum pressure a system is permitted to experience under fault conditions limited by safety devices when operated at the design pressure.

**Design Minimum Pressure (DMP):** The minimum pressure that may occur at the end of any service pipe at the time of system design flow rate under extreme gas supply and maintenance conditions.

Design Pressure (DP): The pressure on which design calculations are based.

**ECV:** Emergency Control Valve.

**ESP:** Emergency Service Provider.

**Gas fitting:** Pipework, valves, ECV's, regulators, slam shuts, relief valves, meters, apparatus, appliances.

Gas Safe Register: Organisation holding the registration details of gas installers.

**Gas Supply Arrangements:** The physical provision of gas supply pipes and the associated Network Code contractual agreement with the registered system for a gas capacity (peak flow) to be available at the outlet of the ECV which terminates the gas supply pipe.

**Lowest Operating Pressure (LOP):** Minimum pressure which a system is designed to experience under normal operating conditions.

Maximum Incidental Pressure (MIP): Maximum pressure which a system is permitted to experience under fault conditions, limited by safety devices.

**Maximum Operating Pressure (MOP):** Maximum pressure at which a system can be operated continuously under normal operating conditions.

**Meter Installation ("mi" subscript):** The position on the gas system where the pressure reading is taken where this is on the meter installation.

Metering Pressure: Pressure at which the meter is intended to measure the volume of gas supplied.

**Nationally Accredited Certification Body:** The organisation responsible for the administration of a Nationally Accredited Certification Scheme.

**Nationally Accredited Certification Scheme:** The scheme accredited by the United Kingdom Accreditation Service (UKAS) for assessing the competency of gas operatives to undertake specific categories of work on gas fittings.

**Ofgem Approved Meter Installer (OAMI):** An organisation which performs meter installation work and is registered with Gas Safe Register as a registered installer in accordance with regulation 3(3) of GS(I&U)R and with Ofgem under the terms of the Standard Supplier Licence Conditions. An OAMI can be contracted to carry out Meter Work for a Supplier, Shipper, a GT or a Gas User (or group of Gas Users) and may be an independent organisation or part of a Supplier, Shipper or GT organisation.

**Operating pressure range:** Range of pressures which a gas system operates under normal conditions.

**Primary Meter Installation:** The apparatus through which a consumer takes a gas supply into their premises, which includes the meter, filter (if fitted), regulator, interconnecting pipe work, semi-rigid connection, fittings and all necessary supports.

**Standard Appliance:** A domestic or non-domestic appliance manufactured to a National or European Standard and having a normal operating pressure of 20 mbar.

**Upstream ("u" subscript):** The position on the gas system where the pressure reading is taken where this is upstream of the meter installation.

# APPENDIX C: Request for Authorisation to set & seal regulators forms.

FORM C1

GT Ref:		MAM Ref:	Date:		
Line number	ber low pressure installations with a badged capacity not exceeding 6m³/hour.				
	Is this request made as par	t of smart metering? 🗌 Yes 🗌 No			
1	Name and address of organisation submitting this request and installing the meter installation (Correspondence Address).		OAMI Number (If applicable) MAM Registration Number.(Mandatory)		
2	Name and address of OAMI requesting Authorisation to break a seal, set and seal the meter regulator.		OAMI number (Mandatory)		
3	Section A to be complete	d by the organisation requesting to	o install the meter installation.		
4	We warrant that any met this organisation followin Authorisation will meet th	g receipt of [ Insert	ined above installed or modified by name of GT ] Letter of		
5	The meter installation & housing are designed and will be installed to comply with the requirements of BS6400-1:2006				
6	The meter installation is capable of sustaining a Design Maximum Incidental Pressure $(DMIP_u)$ of 200 mbar at the inlet of the meter installation without jeopardising the integrity of any connected gas fittings, and will have an associated Design Pressure that must be $\geq$ (DP <sub>u</sub> ) of 75mbar.				
7	The meter installation will ensure that for gas flow rates greater than 5% of the maximum allowable flow rate, the operating pressure at the outlet of the meter installation is maintained between $15 - 25$ mbar when the pressure at the inlet of the meter installation is between a DmP u 19 mbar and MOPu 75 mbar.				
8		lation will meet the requirements ith Section 17 of the Gas Act.	Schedule 2B of the Gas Act with		
9	registration and that the		tion has the appropriate Gas Safe ork holds an appropriate and valid tification Scheme or ACOP.		
10		anisation is not OAMI registered, t with the Gas Suppliers Standard	the installation will be inspected by Licence Conditions.		
11	Signed:	(By organis	ation installing meter installation)		
12	Name:	Date			
13	Position in Organisatio	n:			
GT Ref:		Date:			
14	Section B to be complete and seal the meter regula	ed by the organisation requesting <i>l</i> ator.	Authorisation to break a seal, set		
15	The regulator will be set	to ensure a metering pressure (F	P <sub>mi</sub> ) of (see note 1) ] mbar		
16	The regulator lock up pr	essure will not exceed (s	see note 1) [ ] mbar		
17	Under all circumstances installation pipe work, ga	s (including zero flow) the meter in as fittings and any appliances from mbar. (see note 2)	nstallation will protect the		

23	Position in Organisation e.g. Responsible Engineer/Manager
22	Name: Date:
21	Signed: (By organisation requesting to break a seal, set and seal the meter regulator).
20	I confirm that this organisation is an OAMI and request Authorisation to break a seal, set and seal the meter regulator. I also confirm that a Gas Safe registered person with appropriate competencies for this category of work will ensure that the meter regulator, when installed and put to work will not exceed the values stated above. In the event that the meter regulator is adjusted it will be subsequently sealed with this organisation's seal marked with our OAMI registration number to prevent unauthorised adjustment.
19	The company responsible for undertaking any setting or adjustment has the appropriate Gas Safe registration and that the individual who undertakes the work holds an appropriate certificate of competence under Nationally Accredited Certification Scheme or ACOP.
18	The meter installation will be clearly labelled with its metering pressure.

Note 1: Reference should be made to Appendix I for appropriate values.

Note 2: On low pressure installations where the metering pressure is 21mbar, this figure should be the lock-up pressure for the meter regulator, where the upstream network is in a fault condition and the Service Pressure is MIPu.

# FORM C2

GT Ref:	1	MAM Ref:	Date:
Line number		on to undertake the setting a llations with a badged capacit	nd sealing of meter regulators on ty not exceeding 6m³/hour.
	Is this request made as part	of smart metering?  Yes  N	0
1	Name and address of organisation submitting this request and installing the meter installation (Correspondence Address).	-	OAMI Number (If applicable) MAM Registration Number.(Mandatory)
2	Name and address of OAMI requesting Authorisation to break a seal and set and seal the meter regulator and any associated pressure control and protection devices.		OAMI number (Mandatory)
3	Section A to be completed	I by the organisation requesting	to install the meter installation.
4	We warrant that any meter installation of the category defined above installed or modified by this organisation following receipt of [ Insert name of GT ] Letter of Authorisation will meet the following conditions:		
5	The meter installation & housing are designed and will be installed to comply with the requirements of the BS6400-2:2006.		
6	The meter installation will be regulated and the pressure control and protection arrangements of the installation will comply with BS6400-2:2006 Fig [ ] (See note 1)		
7	(DMIP <sub>u</sub> ) at the inlet of the	capable of sustaining a Design I meter installation of 2.7 bar with s and will have an associated D	hout jeopardising the integrity of
8	The meter installation will ensure that at gas flow rates greater than 5% of the maximum allowable flow rates, the operating pressure at the outlet of the meter installation is maintained between $15 - 25$ mbar when the pressure at the inlet of the meter installation is between the DmP <sub>u</sub> [ ] and MOP <sub>u</sub> [ ] ( <i>see note2</i> ).		
9		ation will meet the requirements the Section 17 of the Gas Act.	Schedule 2B of the Gas Act with
10	That the company responsible for undertaking the installation has the appropriate Gas Safe registration and that the individual who undertakes the work holds an appropriate and valid certificate of competence under Nationally Accredited Certification Scheme or ACOP.		
11	In the event that my organisation is not OAMI registered, the installation will be inspected by an OAMI in accordance with the Gas Suppliers Standard Licence Conditions.		
12	Signed:	By organ	nisation installing meter installation
13	Name:	Date:	
14	Position in organisatior		

Note 1: The applicant should state what pressure control Fig number taken from BS6400-2:2006 is to be used and a separate application shall be required for each regulator type e.g. Fig 1A or 1B.

Note 2: Reference to Appendix I table 4

T Refe	rence Number:	Date:
15	Section B to be completed by the organd seal the meter regulator.	panisation requesting Authorisation to break a seal, set
16	The regulator will be set to ensure a	A Metering Pressure (Pmi) of (see note 1) [ ] mbar
17	The regulator lock up pressure will	not exceed (see note 1) [ ] mbar
18	The relief valve will be set to open a	t a pressure of (see note 1) [ ] mbar
19	The final safety device will be set at	a pressure of (see note 1) [ ] mbar
20		zero flow) the meter installation will protect the and any appliances from being exposed to pressures (see note 2)
21		labelled with its metering pressure, the pressure any pressure of any final protection device.
22	Gas Safe registration and that the in	taking any setting or adjustment has the appropriate ndividual who undertakes the work holds an appropriat ionally Accredited Certification Scheme or ACOP.
23	set and seal the meter regulator an devices. I also confirm that a Gas S this category of work will ensure tha not exceed the values stated above	OAMI and request Authorisation to break a seal and d any associated pressure control and protection afe registered person with appropriate competencies for t the meter regulator, when installed and put to work w . In the event that the meter regulator is adjusted it will ganisation's seal marked with our OAMI registration ustment.
24	Signed: (By organisation requesting to brea	k a seal, set and seal the meter regulator).
25		_
	Name:	Date:
26		
	Position in Organisation e.g. Respo	nsible Engineer/Manager

Note 1: Reference should be made to Appendix I for appropriate values or BS6400-2-2006..

Note 2: Insert the Maximum Incidental Pressure (MIP) of the final protection device (refer to BS6400-2:2006).

# FORM C3A

GT Ref:		MAM Ref:		Date:	
Line number					
1	Name And address of organisation submitting this request and installing the meter installation. (Correspondence Address)		OAMI Number (If applicable) MAM Registration		
2	Name and address of OAMI requesting Authorisation to break a seal, set and seal the meter regulator.		Number.(Mandatory) OAMI number (Mandatory)		
3	Section A to be complete	ed by the organisation reque	esting to	install the meter	er installation.
4	this organisation followi	eter installation of the catego ng receipt of [ the following conditions:		ed above insta ame of GT	alled or modified by ] Letter of
5	The meter installation & housing are designed and will be installed to comply with the requirements of IGEM/GM/6.				
6	The meter installation is capable of sustaining a Design Maximum Incidental Pressure $(DMIP_u)$ of 200 mbar at the inlet of the meter installation without jeopardising the integrity of any connected gas fittings, and will have an associated Design Pressure that must be $\geq$ (DP <sub>u</sub> ) of 75mbar.				
7	The meter installation will ensure that gas flow rates greater than 5% of the maximum allowable flow rates, the operating pressure at the outlet on the meter installation is maintained between $15 - 25$ when the pressure at the inlet of the meter installation is between DmP $_{\rm u}$ 19 mbar and MOP $_{\rm u}$ 75 mbar.				
8		Illation will meet the require vith Section 17 of the Gas A		chedule 2B of	the Gas Act with
9	That the company responsible for undertaking the installation has the appropriate Gas Safe registration and that the individual who undertakes the work holds an appropriate and valid certificate of competence under Nationally Accredited Certification Scheme or ACOP.				
10	In the event that my organisation is not OAMI registered, the installation will be inspected by an OAMI in accordance with the Gas Suppliers Standard Licence Conditions.				
11	Signed:	Ву	organis	ation installing	meter installation
12	Name:	Date	):		
13	Position in Organisati	on:			

GT Re	eference Number: Date:			
14	Section B to be completed by the organisation requesting Authorisation to break a seal, set and seal the meter regulator.			
15	The regulator will be set to ensure a metering pressure of (P <sub>mi</sub> ) (see note 1) [ ] mbar			
16	The regulator lock up pressure will not exceed   (see note 1)   [] mbar			
17	Under all circumstances (including zero flow) the meter installation will protect the installation pipe work, gas fittings and any appliances from being exposed to pressures greater than [ 30 ] mbar. (see note 1)			
18	The meter installation will be clearly labelled with its metering pressure.			
19	The company responsible for undertaking any setting or adjustment has the appropriate Ga Safe registration and that the individual who undertakes the work holds an appropriate certificate of competence under Nationally Accredited Certification Scheme or ACOP.			
20	I confirm that this organisation is an OAMI and request Authorisation to break a seal, set an seal the meter regulator. I also confirm that a Gas Safe registered person with appropriate competencies for this category of work will ensure that the meter regulator, when installed a put to work will not exceed the values stated above. In the event that the meter regulator is adjusted it will be subsequently sealed with this organisation's seal marked with our OAMI registration number to prevent unauthorised adjustment.			
21	Signed: (By organisation requesting to break a seal, set and seal the meter regulator).			
22	Name: Date:			
23	Position in Organisation e.g. Responsible Engineer/Manager			

Note 1: On low pressure installations where the metering pressure is 21mbar, this figure should be the lock-up setting for the meter regulator, where the upstream network is in a fault condition and the Service Pressure is MIPu.

## Form C3B

GT Ref:		MAM Ref:		Date:		
Line number	Request for Authorisation to undertake the setting and sealing of meter regulators on low pressure, standard, installations with a badged capacity exceeding 40m <sup>3</sup> /hour but not exceeding 1076m <sup>3</sup> /hour (standard pressure service)					
	Is this request made as pa	art of advanced metering?	Yes 🔲 I	No		
1	Name And address of organisation submitting this request and installing the meter installation. (Correspondence		(If applic MAM Registr	ation		
	Address)		NUMDE	er.(Mandatory)		
2	Name and address of OAMI requesting Authorisation to break a seal, set and seal the meter regulator.		OAMI r (Mandate	number ory)		
3	Section A to be complet	ed by the organisation reque	esting to	install the meter	er installation.	
4	We warrant that any meter installation of the category defined above installed or modified by this organisation following receipt of [ Insert name of GT ] Letter of Authorisation will meet the following conditions:					
5	The meter installations requirements of IGEM/	& housings are designed ar GM/6.	nd will be	e installed to co	omply with the	
6	(DMIP <sub>u</sub> ) of 200 mbar at	s capable of sustaining a De the inlet of the meter install ngs, and will have an associa	lation wit	thout jeopardis	ing the integrity of	
7	allowable flow rates, the	vill ensure that gas flow rate e operating pressure at the 5 - 25 when the pressure at ar and MOP <sub>u</sub> 75 mbar.	outlet on	the meter inst	allation is	
8		allation will meet the require with Section 17 of the Gas A		chedule 2B of	the Gas Act with	
9	registration and that the	onsible for undertaking the i e individual who undertakes ce under Nationally Accredit	the worl	k holds an app	ropriate and valid	
10		ganisation is not OAMI regis with the Gas Suppliers Sta				
11	Signed:	Ву	organisa	ation installing	meter installation	
12	Name:	Date	e:			
13	Position in Organisati	on:				

GT Re	ference Number: Date:
14	Section B to be completed by the organisation requesting Authorisation to break a seal, set and seal the meter regulator.
15	The regulator will be set to ensure a metering pressure of (P <sub>mi</sub> ) (see note 1) [] mbar
16	The regulator lock up pressure will not exceed   (see note 1)   [ ] mbar
17	Under all circumstances (including zero flow) the meter installation will protect the installation pipe work, gas fittings and any appliances from being exposed to pressures greater than [ 30 ] mbar. (see note 1)
18	The meter installation will be clearly labelled with its metering pressure.
19	The company responsible for undertaking any setting or adjustment has the appropriate Gas Safe registration and that the individual who undertakes the work holds an appropriate certificate of competence under Nationally Accredited Certification Scheme or ACOP.
20	I confirm that this organisation is an OAMI and request Authorisation to break a seal, set and seal the meter regulator. I also confirm that a Gas Safe registered person with appropriate competencies for this category of work will ensure that the meter regulator, when installed and put to work will not exceed the values stated above. In the event that the meter regulator is adjusted it will be subsequently sealed with this organisation's seal marked with our OAMI registration number to prevent unauthorised adjustment.
21	Signed: (By organisation requesting to break a seal, set and seal the meter regulator).
22	Name: Date:
23	Position in Organisation e.g. Responsible Engineer/Manager

Note 1: On low pressure installations where the metering pressure is 21mbar, this figure should be the lock-up setting for the meter regulator, where the upstream network is in a fault condition and the Service Pressure is MIPu.

# FORM C4A

GT Ref:		MAM Ref:		Date:	
Line number	Request for Authorisati associated pressure co or higher pressure inst	ntrol and protection de	vices on	a low pressu	ire, non-standard
1	Name and address of organisation submitting this request and installing the meter installation. (Correspondence Address)		(If appli MAM Regis	Number icable) tration er.(Mandatory)	
2	Name and address of OAM requesting Authorisation to break a seal and set and seal the meter regulator and any associated pressure control and protection devices.		OAMI (Manda	number atory)	
3	Address where meter installation is to be installed.				
4	MPRN or Confirmed Quotation Reference.				
5	Section A to be completed	d by the organisation requ	lesting to	install the met	er installation
6	We warrant that this meter modified by this organisa Letter of Authorisation wi	tion following receipt of [			installed or me of GT ]
7	The meter installation & h requirements of the follow				nply with the
8	The meter installation wil arrangements of the insta		essure co	ntrol and prote	ection ] (see note 1)
9	The meter installation is of inlet of the meter installat connected gas fittings, ar (DP <sub>u</sub> ) (see note 2)	tion of [ ] (DMIP <sub>u</sub> )	without je	opardising the	integrity of any
10	The meter installation wil allowable flow rate, the C maintained between 15 – between DmP <sub>u</sub> [ ] and	perating Pressure at the	outlet on sure at the	the meter inst	tallation is
11	The meter and the install respect to compliance wir Does the consumer inten <b>know</b> ] Delete as appropr	th Section 17 of the Gas d to use a compressor o	Act. r booster	on the gas su	
12	The company responsible Safe registration and that certificate of competence	t the individual who unde	rtakes the	work holds a	n appropriate
13	In the event that my orga by an OAMI in accordance				
14	Signed:	В	y organisa	ation installing	meter installation
15	Name:	Da			
16		Du			

	erence Number:	Date	:	
18	Section B to be completed by the organisation reque seal the meter regulator and any associated pressur			
19	The regulator will be set to ensure a metering pres	sure of (P <sub>mi</sub> )	[	] mbar
20	The regulator lock up pressure will not exceed	(see note 3)	[	] mbar
21	The relief valve will be set to open at a pressure of	(see note 3)	[	] mbar
22	The final safety device will be set at a pressure of	(see note 3)	[	] mbar
	For twin stream and installations with a monito	r regulator.		
23	The set point of the standby stream active		[	] mbar
24	The set point of the monitor regulator if applicable		[	] mbar
25	Under all circumstances (including zero flow) the m installation pipe work, gas fittings and any appliance mbar (MIP <sub>mi</sub> ). Any bypass arrangements, if fitted, w met.(see note 3)	es from pressures	greate	er than [ ]
26	The meter installation will be clearly labelled with it relief valve will open and the limiting pressure of th			pressure the
	Teller valve will open and the limiting pressure of th	e final protection de	evice.	
27	The company responsible for undertaking any setti Safe registration and that the individual who under certificate of competence under Nationally Accredit	ng or adjustment h akes the work hold	as the Is an a	appropriate
27 28	The company responsible for undertaking any setti Safe registration and that the individual who under	ng or adjustment h akes the work hold ed Certification Sc uest Authorisation f ure control and safe propriate competen ssociated pressure eed the values sta quently sealed with	as the ls an a heme to brea ety dev cies fo e contr ted ab this o	appropriate or ACOP. ak a seal, set and vices. I also or this category of ol and safety oove. In the event rganisation's
	The company responsible for undertaking any setti Safe registration and that the individual who under certificate of competence under Nationally Accredit I confirm that this organisation is an OAMI and req seal the meter regulator and any associated press confirm that a Gas Safe registered person with app work will ensure that the meter regulator and any a devices, when installed and put to work will not exc that the meter regulator is adjusted it will be subset	ng or adjustment h akes the work hold ed Certification Sc uest Authorisation t ure control and safe propriate competen ssociated pressure eed the values sta quently sealed with prevent unauthoris	as the ls an a heme to breat ety dev cies for contr ted ab this o ed adj	appropriate or ACOP. ak a seal, set and vices. I also or this category of ol and safety oove. In the event rganisation's ustment.
28	The company responsible for undertaking any setti Safe registration and that the individual who under certificate of competence under Nationally Accredit I confirm that this organisation is an OAMI and requise al the meter regulator and any associated press confirm that a Gas Safe registered person with app work will ensure that the meter regulator and any a devices, when installed and put to work will not exc that the meter regulator is adjusted it will be subset seal marked with our OAMI registration number to Signed:	ng or adjustment h akes the work hold ed Certification Sc uest Authorisation f are control and safe propriate competen ssociated pressure eed the values sta quently sealed with prevent unauthoris	as the ls an a heme to breat ety dev cies for contr ted ab this o ed adj	appropriate or ACOP. ak a seal, set and vices. I also or this category of ol and safety oove. In the event rganisation's ustment.

Note 1: State which Figure taken from Appendix 8 of IGE/GM/8 Part 1 will be used for Regulator design and meter type e.g. Fig 24 (diaphragm meter), Fig 25 (RPD), Fig 26 (Turbine), or submit a site specific drawing.

Note 2: Determine the DMIP, DP, DmP and MOP from Appendix I, Table 4.

Note 3: Reference should be made to Appendix I of this document or IGE/GM/8 Part 3 Table 1 for appropriate values.

Note 4: Insert the appropriate pressure of the final protection device, normally the set pressure. On low pressure installations where the metering pressure is 21mbar, this figure should be the lock-up setting for the meter regulator, where the upstream network is in a fault condition and the Service Pressure is MIPu. This would apply for example, where there was a standard installation with a by-pass.

Note 5: On installations incorporating multiple regulators, the lockup to be declared is that of the highest set regulator, e.g. A monitor where fitted.

# FORM C4B

GT Ref:	1	MAM Ref:	Date:	
Line number	associated pressure co	on to undertake the settin ntrol and protection devi allation with a metering p	ces on a low pressu	ure, non-standard
1	Name and address of organisation submitting this request and installing the meter installation (Correspondence Address)		OAMI Number (If applicable) MAM Registration	
2	Name and address of OAMI requesting Authorisation to break a seal and set and seal the meter regulator and any associated pressure control and protection devices.		Number.(Mandatory) OAMI number (Mandatory)	
3	Address where meter installation is to be installed			
4	MPRN or Confirmed Quotation Reference			
5	Section A to be completed	by the organisation reques	ting to install the met	ter installation
6	modified by this organisat	r installation of the categor tion following receipt of [ I meet the following conditi	Insert na	installed or me of GT ]
7	The meter installation & housing are designed and will be installed to comply with the requirements of the following standards IGE/GM/4 and IGE/TD/13, or IGE/GM/8, as applicable.			
8		be unregulated [ <b>Yes / No]</b> obtain and attach a copy o &U)R.		
9		be regulated and the pres		ection
10	at the inlet of the meter in	be capable of sustaining a stallation of ( <b>DMIP</b> <sub>u</sub> )[ ] m s and will have an associate	bar without jeopardis	sing the integrity of
11	allowable flow rate, the op maintained between[			allation is meter installation is
12	The meter and the installar respect to compliance wit Does the consumer intended	ation will meet the requiren h Section 17 of the Gas Ac d to use a compressor or b ate and provide details wh	nents Schedule 2B of ct. poster on the gas su	f the Gas Act with
13	Safe registration and that	e for undertaking any settin the individual who underta under Nationally Accredite	kes the work holds a	an appropriate
14	In the event that my organ by an OAMI in accordance	nisation is not OAMI Regis e with the Gas Suppliers S	tered, the installation tandard Licence Cor	will be inspected
15	Signed:	By c	organisation installing	meter installation
16	Name:	Date		
17	Position in Organisation	ו:		

	erence Number:		Date	:	
18	Section B to be completed by the organisa seal the meter regulator and any associate				
19	The regulator will be set to ensure a meter	ering pressure	of (P <sub>mi</sub> )	[	] mbar
20	The regulator lock up pressure will not ex	ceed	(see note 3)	[	] mbar
21	The relief valve will be set to open at a pr	essure of	(see note 3)	[	] mbar
22	The final safety device will be set at a pre	essure of	(see note 3)	[	] mbar
	For twin stream and installations with	a monitor reg	julator.		
23	The set point of the standby stream active	e		[	] mbar
24	The set point of the monitor regulator if a	pplicable		[	] mbar
25	Under all circumstances (including zero fl installation pipe work, gas fittings and any mbar (MIP <sub>mi</sub> ). Any bypass arrangements, met.(see note 3)	y appliances fr	om pressures	greate	er than [ ]
26	The meter installation will be clearly label relief valve will open and the limiting pres				pressure the
27	The company responsible for undertaking Safe registration and that the individual w certificate of competence under National	ho undertakes	s the work hold	ls an a	appropriate
28	I confirm that this organisation is an OAM seal the meter regulator and any association				
	confirm that a Gas Safe registered person work will ensure that the meter regulator a devices, when installed and put to work w that the meter regulator is adjusted it will seal marked with our OAMI registration n	n with appropr and any assoc vill not exceed be subsequen	iate competen siated pressure the values sta tly sealed with	cies fo contr ted ab this o	or this category of ol and safety pove. In the event rganisation's
29	confirm that a Gas Safe registered person work will ensure that the meter regulator devices, when installed and put to work we that the meter regulator is adjusted it will	n with appropr and any assoc vill not exceed be subsequen umber to prev	iate competen iated pressure the values sta tly sealed with ent unauthoris	cies fo e contr ted ab this o ed adj	or this category of ol and safety pove. In the event rganisation's ustment.
29 30	confirm that a Gas Safe registered person work will ensure that the meter regulator devices, when installed and put to work with that the meter regulator is adjusted it will seal marked with our OAMI registration n Signed:	n with appropr and any assoc vill not exceed be subsequen umber to prev	iate competen iated pressure the values sta tly sealed with ent unauthoris	cies fo e contr ted ab this o ed adj	or this category of ol and safety pove. In the event rganisation's ustment.

Note 1: State which Figure taken from appendix 8 of IGE/GM/8 Part 1 will be used for Regulator design and meter type e.g. Fig 24 (diaphragm meter), Fig 25 (RPD), Fig 27 (Turbine), or submit a site specific drawing.

Note 2: Determine the DMIP, DP, DmP and MOP from Appendix I, Table 4.

Note 3: Reference should be made to IGE/GM/8 Part 3 for appropriate values.

Note 4: On installations incorporating multiple regulators, the lockup to be declared is that of the highest set regulator, e.g. A monitor where fitted.

# CUSTOMER WARRANT TYPE A.

GT Ref:	MAM Ref:	Date:	
Customer warrant for submission wit	h GT2 form C4B. (Request for	Authorisation to undertake the setting	and sealing of
		vices on a low pressure, non-standard o	or higher
pressure installation with a metering	pressure other than 21 mbar).		
		MAM	
Name and address of organisation		registration	
submitting this request and installing	the	number or	
meter installation:		OAMI number	
Name and address of OAMI request	•		
Authorisation to break a seal, set an		OAMI Number	
the meter regulator and any associa			
pressure control and protection devi	ces(s)		
Address where meter installation is t installed.	o be		
MPRN or Confirmed Quotation Refe	rence.		
This section to be completed by the	he organisation requesting	to install the meter installation.	
		lvise you of the pressures that the me	ter installation
will provide under operating conditio			
Design Minimum Pressure (DmP <sub>mi</sub> )			mbar
Minimum Outlet Pressure under extr	reme conditions		
Lowest Operating Pressure (LOP <sub>mi</sub> )			mbar
Normal Outlet Pressure			mbar
Metering Pressure (Pressure Reque			mbai
Peak Level / Temporary Operating F			mbar
Maximum pressure at the meter inst		conditions (TOP <sub>mi</sub> is the term when a	
monitor regulator is fitted, otherwise			
Maximum Incidental Pressure (MIP <sub>m</sub> Maximum Outlet Pressure under ext			mbar
This section to be completed by a			. ( ( . )
		t your downstream system is capable	
		ng your responsible engineer will need	d to consider the
following aspects of the design of yo			
operate safely.	ssure in the range LOPmi – M	OP <sub>mi</sub> all connected equipment/appliar	ices have to
	mont has been adequately a	trength tested to withstand pressure u	n to and
including the MIPmi indicated above			p to and
		ve been designed in accordance with	the recognised
	•	ated plant are compatible with the range	0
		perate safely under all of the above co	
		nvalidate this declaration, if this is not	possible, prior to
making any such modifications we w	vill request that the meter inst	allation be modified.	
We confirm that the operational line	mit of our downstream syst	em are:	
Design Minimum Pressure (DMPc)			mba
Lowest Operating Pressure (LOPc)			mba
Maximum Operating Pressure MOP			mba
Strength Test Pressure (STPc) Note			mbai
Maximum Incidental (Reverse) Pres			mbai
Signed	On behalf of the Consumer		
Name Position in Organisation		Date	
Company Name and Address:			
company Name and Address.			

Note 1 : Where the exchange is on a like for like basis with no changes to pressure settings use Customer Warrant Type B.

# CUSTOMER WARRANT TYPE B METER EXCHANGES.

GT Ref: MAM	Ref:	Date:		
Customer warrant for submission with GT		24101		
(Request for Authorisation to undertake th		eter regulator, as	sociated	pressure
control and protection devices on a low pr				
pressure other than 21 mbar).	· · ·	•		•
		MAM		
Name and address of organisation		registration		
submitting this request and installing the		number or		
meter installation:		OAMI number		
Name and address of OAMI requesting				
Authorisation to break a seal, set and seal		OAMI Number		
the meter regulator and any associated				
pressure control and protection devices(s)				
Address where meter installation is to be				
installed.				
MPRN or Confirmed Quotation Reference.				
This section is to be completed by the org				
For the attention of the "Gas User", the MA		e pressures that t	he meter	installation
will provide under operating conditions. Thes	e being:			
Design Minimum Pressure (DmP <sub>mi</sub> )				
Minimum Outlet Pressure under extreme con	ditions.			mbar
Lowest Operating Pressure (LOP <sub>mi</sub> )				mbar
Normal Outlet Pressure				mour
Metering Pressure				mbar
Peak Level / Temporary Operating Pressure				
Maximum pressure at the meter installation of		$OP_{mi}$ is the term with	hen a	mbar
monitor regulator is fitted, otherwise PLOP <sub>mi</sub> i	s used).			
Maximum Incidental Pressure (MIP <sub>mi</sub> ) Maximum Outlet Pressure under extreme con	aditiona			mbar
The MAM signs to confirm that no changes		tings and that th	o installa	tion predates
2005 and that the installation is fit for purp		tings and that the	c motana	tion predates
	alf of the Meter Asset Manager			
Name	6	Date		
Position in Organisation				
, , , , , , , , , , , , , , , , , , ,	to up in writing that your downs	troom avetem is a	onoble of	aafaly
In return we are required to ask you to confirn operating under all of the above supply condit				
following aspects of the design of your downs		unsible engineer v	viii neeu t	
With the meter installation outlet pressure in t		nnected equinmer	nt/annlian	ces have to
operate safely.			louppilai	
All downstream pipe-work and equipment has	been adequately strength tested	d to withstand pres	ssure up	to and
including the MIPmi indicated above (In accor				
We warrant that the downstream pipe-work &		igned in accordan	ce with th	e recognised
industry standards. The design of both the pi				
you have advised me the meter installation wi				
We will ensure that any future modification to			s is not po	ssible, prior to
making any such modifications we will reques		odified.		
U	alf of the Consumer	Dete		
Name		Date		
Position in Organisation Company Name and Address:				
Company Name and Address.				

APPENDIX D: GT check lists for reviewing a Request for Authorisation.

Form D1 Check list for reviewing a Request for Authorisation to undertake the setting and sealing of meter regulators on low pressure (LP) standard meter installations with badged meter capacity not exceeding 6m<sup>3</sup>/hr.

#### Form D1

GT Reference r	number		
	ress of organisation submitting this request and eter installation. ce Address)		
	ress of organisation requesting Authorisation to et and seal the meter regulator.		
Date of the Rec	quest for Authorisation		
Appendix C1 Line No	Checks/criteria		Checks/ criteria satisfied
	Has the 'Request for Authorisation' been submit	ted on form	Yes / No
11 & 21	Has the request been signed?		Yes / No
1	Has the request been submitted by a Registered MAM? (Check OFGEM web site)		Yes / No
2	Has the Request for Authorisation to break a sea the meter regulator and any associated pressure protection device(s) been made by an OAMI? (Check OFGEM web site)		Yes / No
4	Is the application being made to the correct GT?		Yes / No
5	Have the meter installation & housing been design modified to comply with BS6400-1:2006?	gned or	Yes / No
6, 7, 8, 9, 10, 18,19 & 20	Has this clause remained unaltered (i.e. no addit deletions made)?	ions or	Yes / No
15, 16 & 17	Is the value inserted into the clause appropriate?	>	Yes / No
Comments:			

Form D2 Check list for reviewing a Request for Authorisation to undertake the setting and sealing of meter regulators on medium pressure (MP) standard meter installations with badged meter capacity not exceeding 6m<sup>3</sup>/hr.

Form	D2	

	uest for Authorisation		
	ress of organisation submitting this request and eter installation. ce Address)		
	ress of Organisation requesting Authorisation to at and seal the meter regulator.		
Application Ref	erence Number		
Appendix C2 Line No	Checks/criteria		Checks/ criteria satisfied
	Has the 'Request for Authorisation' been submitt C2?	ed on form	Yes / No
12 & 24	Has the request been signed?		Yes / No
1	Has the request been submitted by a Registered (Check OFGEM web site)	MAM?	Yes / No
2	Has the Request for Authorisation to break a sea the meter regulator and any associated pressure protection device(s) been made by an OAMI? (check OFGEM web site)		Yes / No
4	Is the application being made to the correct GT?		Yes / No
5	Have the meter installation & housing been desig modified to comply with BS6400-2:2006?	gned or	Yes / No
6	Is the pressure control and protection arrangeme (check figure stated i.e. Fig 1A or 1B)	ent acceptable?	Yes / No
8	Are the DMP and MOP consistent with one of the Medium Pressure tier?	e options for a	Yes / No
7, 9, 10, 11,	Has this clause remained unaltered (i.e. no addit deletions made)?	ions or	Yes / No
21, 22 & 23	r	)	

Form D3A Check list for reviewing a Request for Authorisation to undertake the setting and sealing of meter regulators on low pressure (LP) standard meter installations with badged meter capacity exceeding 6m<sup>3</sup>/hr but not exceeding 40m<sup>3</sup>/hr (Standard pressure service).

# Form D3A

	ress of Organisation requesting Authorisation to et and seal the meter regulator.		
Date of the Red	quest for Authorisation		
Application Ref	erence Number		
Appendix C3A Line No	Checks/criteria		Checks/ criteria satisfied
	Has the 'Request for Authorisation' been submitted on form C3A/B?		Yes / No
11 & 21	Has the request been signed?		Yes / No
1	Has the request been submitted by a Registered MAM? (Check OFGEM web site)		Yes / No
2	Has the Request for Authorisation to break a seal, set and seal the meter regulator and any associated pressure control and protection device(s) been made by an OAMI? (check OFGEM web site)		Yes / No
4	Is the application being made to the correct GT?		Yes / No
5	Have the meter installation & housing been designed or modified to comply with IGEM/GM/6?		Yes / No
6	Is the pressure control and protection arrangement acceptable? (check figure stated)		Yes / No
7, 8, 9, 10, 18,19 & 20	Has this clause remained unaltered (i.e. no additions or deletions made)?		Yes / No
15, 16 & 17	Is the value inserted into the clause appropriate?		Yes / No

Form D3B Check list for reviewing a Request for Authorisation to undertake the setting and sealing of meter regulators on low pressure (LP) standard meter installations with badged meter capacity exceeding 40m<sup>3</sup>/hr but not exceeding 1076m<sup>3</sup>/hr (Standard pressure service).

## Form D3B

	lress of Organisation requesting Authorisation to et and seal the meter regulator.		
Date of the Re	quest for Authorisation		
Application Re	ference Number		
Appendix C3B Line No	Checks/criteria		Checks/ criteria satisfied
	Has the 'Request for Authorisation' been submitt C3A/B?	ed on form	Yes / No
11 & 21	Has the request been signed?		Yes / No
1	Has the request been submitted by a Registered (Check OFGEM web site)	ubmitted by a Registered MAM?	
2	Has the Request for Authorisation to break a seal, set and seal the meter regulator and any associated pressure control and protection device(s) been made by an OAMI? (check OFGEM web site)		Yes / No
4	Is the application being made to the correct GT?		Yes / No
5	Have the meter installation & housing been designed or modified to comply with IGEM/GM/6?		Yes / No
6	Is the pressure control and protection arrangement acceptable? (check figure stated)		Yes / No
7, 8, 9, 10, 18,19 & 20	Has this clause remained unaltered (i.e. no additions or deletions made)?		Yes / No
15, 16 & 17	Is the value inserted into the clause appropriate?		Yes / No

Form D4A Check list for reviewing a Request for Authorisation to undertake the setting and sealing of meter regulators and pressure control devices on Low pressure (LP) Non-Standard or higher pressure meter installations with a metering pressure of 21mbar.

# Form D4A

	ess of Organisation requesting Authorisation set and seal the meter regulator.		
Date of the Req	uest for Authorisation		
Application Refe	rence Number		
Appendix C4A Line No	4A Checks/criteria		Checks/ criteria satisfied
	Has the 'Request for Authorisation' been submitted on form C4A?		Yes / No
14 & 27	Has the request been signed?		Yes / No
1	Has the request been submitted by a Registered MAM? (Check OFGEM web site)		Yes / No
2	Has the Request for Authorisation to break a seal, set and seal the meter regulator and any associated pressure control and protection device(s) been made by an OAMI? (check OFGEM web site)		Yes / No
3, 4	Does the work address match the MPRN / QS number?		Yes / No
6	Is the application being made to the correct GT?		Yes / No
7	Have the meter installation & housing been designed or modified to comply with IGE/GM/8?		Yes / No
8	Is the pressure control and protection arrangement acceptable? (check figure stated)		Yes / No
11	Details of compressors / boosters inserted		Yes / No
12,13,, 24,25,26	Has this clause remained unaltered (i.e. no additions or deletions made)?		Yes / No
9,10,18,19, 20,21,22	Is the value inserted into the clause appropriate	?	Yes / No

Form D4B Check list for reviewing a Request for Authorisation to undertake the setting and sealing of meter regulators and pressure control devices on Low pressure (LP) Non-Standard or higher pressure meter installations with a metering pressure other than 21mbar.

# FORM D4B

	s of Organisation requesting eak a seal, set and seal the meter	
•	est for Authorisation	
Application Refere	ence Number	Checks
Appendix C4B Line No	Checks/criteria	
Has the 'Request for Authorisation' been submitted on f C4B?		Yes / No
	Has a Customer Warrant been submitted?	Yes / No
15 & 27	Has the request been signed?	Yes / No
1	Has the request been submitted by a Registered MAM? (Check OFGEM web site)	
2	Has the Request for Authorisation to break a seal, set and seal the meter regulator and any associated pressure control and protection device(s) been made by an OAMI? (check OFGEM web site)	
3, 4	Does the work address match the MPRN / QS number?	
6	Is the application being made to the correct GT?	
7	Have the meter installation & housing been designed or modified to comply with IGE/GM/4, IGE/GM/8?	
8	If supply is un-regulated is a copy of the exemption certificate included with the application?	
9	Is the pressure control and protection arrangement acceptable? (check figure stated)	
12	Details of compressors / boosters inserted	
12,13,14, ,24,25,26	Has this clause remained unaltered (i.e. no additions or deletions made)?	
10,11,19, 20,21,22,23	Are the value inserted into the clause appropriate?	Yes / No

#### **APPENDIX E: GT meter installation inspections.**

A Competent Person nominated to act on behalf of the GT shall determine whether a meter installation has been installed, modified and/or commissioned in a way that is consistent with the 'Request for Authorisation' and the 'Letter of Authorisation' and whether in the view of that Competent Person the installation is safe.

The inspection will comprise a visual check of the meter installation and appropriate tests to verify the regulator setting is consistent with the 'Letter of Authorisation'.

An acceptable meter installation is one that meets all the '**mandatory criteria**' set out below which should also form the basis of check lists used during the inspection visit (example on next page).

Note: The requirements of GIUSP and RIDDOR will be applied where applicable.

#### Inspection criteria for meter installations (Mandatory GT2 requirements)

MPRN, Meter serial number, Site address, Site contact, Date of installation, Network pressure tier, MAM details, OAMI details, customer warrant are available.

OAMI seals are fitted to Regulators, final safety device, Slam Shut, Creep Relief, By-pass etc.

Impulse line valve is tamper proof or immobilised (see IGE/GM/8 section 13.8)

Installation pressure setting information is provided e.g. DMP, LOP, MOP which are consistent with those stated on the 'Request for Authorisation'.

Pressure setting information is provided for Slam Shut, Creep Relief and Operating Pressure.

Pressure control equipment is suitable for the pressure tier.

OFGEM Meter seal is present and intact (Gas Act requirement).

Installation inlet pressure is indicated (label)

By-pass (if fitted) is regulated.

The 'measured' lock up and operating pressure are consistent with those indicated.

The following labels are fitted and correctly completed: Ex; Line diagram (composite label); Emergency actions; ECV on/off; Remote ECV; \*Secondary meter \*where applicable

In addition to the mandatory criteria listed above, the Competent Person should also record other issues which may impact on the safe operation of the meter installation including;

- Is the ECV correctly designated, suitable for use and fitted with a handle?
- Is there a label fitted to the gas service pipe indicating its status?
- Are 'No Smoking' signs fitted where appropriate?
- Is ventilation provided?
- Is explosion relief provided where appropriate and have transit bolts been removed?
- Is the meter location suitable?
- Is creep relief vented to a safe location?

GT2 Inspect	tion Checkl	ist				
Site Address:						
Contact Name:	Contact N	umbor				
MPRN:	Meter Seria					
Inspection Date:	Installation					
MAM Details:	OAMI Deta					
Inspection criteria for meter installa				ents)	400	070
Network supply pressure tier for this site: (circle)	LP Intern	MP <sup>35</sup> nediate Pre	MP <sup>65</sup> ssure	MP <sup>105</sup>	MP <sup>180</sup> igh Pressu	MP <sup>270</sup>
Warranted Metering Pressure for this site is: 21mbar	(lf c	different pl	ease state	pressure:	ml	bar)
OAMI seals are fitted to Regulators, final safety device, Slam Shut, Creep Relief, By-pass etc.	Pass	Fail	Comments			
Impulse line valve is tamper proof or immobilised (see IGE/GM/8 section 13.8)	Pass	Fail	Comments			
Installation pressure setting information is provided e.g. DMP, LOP, MOP which are consistent with those stated on the 'Request for Authorisation'.	Pass	Fail	Comments			
Pressure setting information is provided for Slam Shut, Creep Relief and Operating Pressure.	Pass	Fail	Comments			
Pressure control equipment is suitable for the pressure tier.	Pass	Fail	Comments			
OFGEM Meter seal is present and intact (Gas Act requirement).	Pass	Fail	Comments			
Installation inlet pressure is indicated (label)	Pass	Fail	Comments			
By-pass (if fitted) is regulated.	Pass	Fail	Comments			
The 'measured' lock up and operating pressure are consistent with those indicated.	Pass	Fail	Comments			
The following labels are fitted and completed (where			el (line diag			ncy Label
applicable):	E	CV On / Of	ff	R	Remote EC	V
In addition to the mandatory criteria listed above, the Compete on the safe operation of the meter installation including;	nt Person s	hould also	record oth	her issues	which may	r impact
Is the ECV correctly designated, suitable for use and fitted with a handle?	Pass	Fail	Comments			
Is there a label fitted to the gas service pipe indicating its status?	Pass	Fail	Comments			
Are 'No Smoking' signs fitted where appropriate?	Pass	Fail	Comments			
Is ventilation provided?	Pass	Fail	Comments			
Is explosion relief provided where appropriate and have transit bolts been removed?	Pass	Fail	Comments			
Is the meter location suitable?	Pass	Fail	Comments			
Is creep relief vented to a safe location?	Pass	Fail	Comments			
Additional Information including details of any RIDDOR, ID, AR	situation fo	ound on sit				
Inspected by:			Signed:			

## APPENDIX F Bypass Authorisation request form

		SATION TO INSTALL A METER BYPA mail be completed in its entirety.	SS				
MPRN or C	Confirmed Quote number:	Name & Address of premises where	bypass to be				
		installed:					
Name and	address of the Gas Supplier:	Post code:					
Has the su	pplier consented to a meter by-pa	ass heing installed?	ES/NO*				
Name and		be responsible for the installation of t					
bypass:							
	stration No:	Installers OAMI Registration Nates of the second states of the second st					
meter by-pass	s in order to avoid a risk of personal injury fault on the meter or metering equipment	or death or damage to property (including prejudi	ce to animal welfare)				
Name: Please print	٤	Signed by:	Date				
	Tick the required box below for the type of premises that the meter bypass is to be installed at.						
a)	Hospitals or hospice						
b)	Institutionalised accommodation schools, and prisons)	n (for example homes for the elderly,					
c)	Premises where prejudice to ar	nimal welfare may occur					
d)		olex plant supporting continuous bulk icultural, baking or other commercial rcumstances					
e)	At meter installations connected	d to:					
	Exceptionally extensive and complex pipework and gas consuming plant multi-occupied premises or a number of discrete consumers (for example a single meter installation serving a block of flats						
Approved/	Rejected* by	GT Position Date					
	GT meter bypass Authorisation Reference Number: Reason for rejection						
* Delete as appl	ropriato						

## Request for meter by-pass Authorisation form.

### APPENDIX G: Form for requesting meter housing / accommodation approval

Request for GT approval for meter housing / accommodation										
GT Reference number:		Date:								
Applicant Name, Address and telephone number:			OAMI Num (if applicabl							
Responsible Engineer: Name address and telephone number:										
General Installation Deta	ils:									
The type of meter installati *delete as appropriate	ion proposed to be insta	alled* e.g. COP/1a, CC	0P/1b, COP/1	С.						
Maximum design capacity			[	] scmh						
Installation inlet design pre *delete as appropriate.	essure		[	] Bar/mbar*						
Housing description										
Туре										
Site Name and Address (if site specific request)										
Technical standards										
Please list the technical sta practice/guidance docume the Installation and housin	ents used to design									
Signed		Date.								
Name and address of organisation										
Position held										

Please attach supporting information as detailed in Appendix G2:

#### APPENDIX G2: Supporting Information required for meter housing approval.

#### Installation pipework and layout

Please attach a clear, dimensioned engineering drawing of the meter installation plan, front and side elevations. Showing details of all pipework and components installed, any vents and relief's fitted.

#### Installation Location and Zoning

Please attach a dimensioned (distances shown in meters) general layout drawing showing the location, clearly indicating:

- The proximity of adjacent building(s), air intakes, etc,
- The location of the meter installation in relation to the site perimeter,
- The location/proximity of the electrical equipment (including instrumentation and any high voltage equipment),
- The hazardous area zone resulting from the installation,
- Any hazardous area resulting from neighbouring plant, etc,
- The means of access to the meter installation,
- The location of any crash barriers,
- The nearest vehicle access,

Supporting documentation will be required showing the results of any hazardous area assessment undertaken, the method used, (IGE/GM/7, IGE/SR/25 etc.)

#### Housing and Ventilation Details

Please attach a clear, dimensioned, engineering drawing showing the plan, front and side elevations of the housing or enclosure, indicating the:

- Size, type and location of ventilation,
- Means of access/egress (including for maintenance activities, component exchange, etc.),
- Security arrangement,
- Details of any explosion relief,
- Position of vent stack terminations,
- Construction materials,
- Position of the electrical equipment within the housing/enclosure (e.g. flow computer/conversion systems, data logger etc.),
- Size of the meter installation floor area (Notional floor area),
- Size of the meter installation housing/accommodation floor area.

#### **Electrical equipment details**

Details of the position of all electrical equipment (to be installed within the housing or immediate surroundings) and their method of protection, i.e. Type n, Intrinsically Safe etc.

# Details of any special arrangements and or precautions that may be required before entering the meter housing/accommodation

Please attach details of the 'key' arrangements for the installation and details of any special precautions that are required before entering the meter housing/accommodation. Confirm that appropriate warning notices will be installed on the housing/accommodation.

Where no special precautions are required a declaration to this effect should be submitted.

#### APPENDIX H: Letters of Authorisation / rejection.

#### Letter E1:

GT Reference number:

<GT Address>

< Application reference number> <Date>

<Name & Address of MAM>

<Name & Address of OAMI (if different)>

<OAMI Registration Number >

<MAM Registration Number >

## Authorisation to undertake the setting and sealing of meter regulators on low pressure (LP) meter installations with badged meter capacity not exceeding 6m<sup>3</sup>/hr.

Thank you for completing the Request for Authorisation, dated < >.

Following our review I can confirm that we have authorised your organisation to break the seal and to set and seal the meter regulator in accordance with the following conditions.

The regulator shall be set to ensure a metering pressure of 21 mbar.

The regulator lock up pressure shall not exceed 30 mbar.

Under all circumstances, including zero flow, the meter installation shall protect the installation pipe work, gas fittings and any appliances from pressures greater than 30 mbar.

The meter installation & housing shall be designed and installed or modified to comply with the requirements of BS6400-1:2006

The meter regulator shall be sealed immediately after any setting or adjustment with a suitable seal within the meaning of the Gas Safety (Installation and Use) Regulations. The seals shall bear the OAMI registration number of your organisation or nominated OAMI.

This Authorisation specifically excludes any validation that the meter satisfies obligations under the Gas Act, Common Law Contract or other with respect to the meter being of a type appropriate for registering the quantity of gas supplied and it's installation in the premises. The responsibility of any design to meet the design objectives stated in your 'Request for Authorisation' and any other statutory obligations will remain with the OAMI acting on behalf of the meter owner as defined in the Gas Act 1986 (as amended 1995) Schedule 2B.

The following reference number has been allocated to this Authorisation, which should be quoted in any subsequent correspondence.

Yours sincerely

Letter E2

GT Reference number:

<GT Address>

< Application reference number> <Date>

<Name & Address of MAM>

<Name & Address of OAMI (if different)>

<OAMI Registration Number >

<MAM Registration Number >

## Authorisation to undertake the setting and sealing of meter regulators on medium pressure (MP) meter installations with badged meter capacity not exceeding 6m<sup>3</sup>/hr. (Fig 1A or 1B)

Thank you for completing the Request for Authorisation, dated < >.

Following our review I can confirm that we have authorised your organisation to break the seal and to set and seal the meter regulator in accordance with the following conditions.

The regulator shall be set to ensure a metering pressure of	21 mbar.
The regulator lock up pressure shall not exceed	30 mbar.
The relief valve shall be set to open at a pressure of	35 mbar.
The final safety device shall be set at a pressure of	40 mbar for Fig 1A design or;
The final safety device shall be set at a pressure of	47.5 mbar for Fig 1B design.

Under all circumstances, including zero flow, the meter installation shall protect the installation pipe work, gas fittings and any appliances from pressures greater than 50 mbar.

The meter installation & housing shall be designed and installed or modified to comply with the requirements of BS6400-2:2006

The meter installation shall be clearly labelled with the metering pressure, final safety device and creep relief setting.

The meter regulator shall be sealed immediately after any setting or adjustment with a suitable seal within the meaning of the Gas Safety (Installation and Use) Regulations. The seals shall bear the OAMI registration number of your organisation or nominated OAMI.

This Authorisation specifically excludes any validation that the meter satisfies obligations under the Gas Act, Common Law Contract or other with respect to the meter being of a type appropriate for registering the quantity of gas supplied and it's installation in the premises. The responsibility of any design to meet the design objectives stated in your 'Request for Authorisation' and any other statutory obligations will remain with the OAMI acting on behalf of the meter owner as defined in the Gas Act 1986 (as amended 1995) Schedule 2B.

The following reference number has been allocated to this Authorisation, which should be quoted in any subsequent correspondence.

Yours sincerely

Letter E3A

GT Reference number:

<GT Address>

< Application reference number> <Date>

<Name & Address of MAM>

<Name & Address of OAMI (if different)>

<OAMI Registration Number >

<MAM Registration Number >

## Authorisation to undertake the setting and sealing of meter regulators on low pressure (LP) meter installations with badged meter capacity exceeding 6m<sup>3</sup>/hr but not exceeding 40m<sup>3</sup>/hr.

Thank you for completing the Request for Authorisation, dated < >.

Following our review I can confirm that we have authorised your organisation to break the seal and to set and seal the meter regulator in accordance with the following conditions.

The regulator shall be set to ensure a metering pressure of 21 mbar.

The regulator lock up pressure shall not exceed 30 mbar.

Under all circumstances, including zero flow, the meter installation shall protect the installation pipe work, gas fittings and any appliances from pressures greater than 30 mbar.

The meter installation & housing shall be designed and installed or modified to comply with the requirements of IGEM/GM/6.

The meter installation shall be clearly labelled with the metering pressure.

The meter regulator shall be sealed immediately after any setting or adjustment with a suitable seal within the meaning of the Gas Safety (Installation and Use) Regulations. The seals shall bear the OAMI registration number of your organisation or nominated OAMI.

This Authorisation specifically excludes any validation that the meter satisfies obligations under the Gas Act, Common Law Contract or other with respect to the meter being of a type appropriate for registering the quantity of gas supplied and it's installation in the premises. The responsibility of any design to meet the design objectives stated in your 'Request for Authorisation' and any other statutory obligations will remain with the OAMI acting on behalf of the meter owner as defined in the Gas Act 1986 (as amended 1995) Schedule 2B.

The following reference number has been allocated to this Authorisation, which should be quoted in any subsequent correspondence.

Yours sincerely

Letter E3B

GT Reference number:

<GT Address>

< Application reference number> <Date>

<Name & Address of MAM>

<Name & Address of OAMI (if different)>

<OAMI Registration Number >

<MAM Registration Number >

## Authorisation to undertake the setting and sealing of meter regulators on low pressure (LP) meter installations with badged meter capacity exceeding 40m<sup>3</sup>/hr but not exceeding 1076m<sup>3</sup>/hr.

Thank you for completing the Request for Authorisation, dated < >.

Following our review I can confirm that we have authorised your organisation to break the seal and to set and seal the meter regulator in accordance with the following conditions.

The regulator shall be set to ensure a metering pressure of 21 mbar.

The regulator lock up pressure shall not exceed 30 mbar.

Under all circumstances, including zero flow, the meter installation shall protect the installation pipe work, gas fittings and any appliances from pressures greater than 30 mbar.

The meter installation & housing shall be designed and installed or modified to comply with the requirements of IGEM/GM/6.

The meter installation shall be clearly labelled with the metering pressure.

The meter regulator shall be sealed immediately after any setting or adjustment with a suitable seal within the meaning of the Gas Safety (Installation and Use) Regulations. The seals shall bear the OAMI registration number of your organisation or nominated OAMI.

This Authorisation specifically excludes any validation that the meter satisfies obligations under the Gas Act, Common Law Contract or other with respect to the meter being of a type appropriate for registering the quantity of gas supplied and it's installation in the premises. The responsibility of any design to meet the design objectives stated in your 'Request for Authorisation' and any other statutory obligations will remain with the OAMI acting on behalf of the meter owner as defined in the Gas Act 1986 (as amended 1995) Schedule 2B.

The following reference number has been allocated to this Authorisation, which should be quoted in any subsequent correspondence.

Yours sincerely

Letter E4A

GT Reference number:

<GT Address>

< Application reference number> <Date>

<Name & Address of MAM>

<Name & Address of OAMI (if different)>

<OAMI Registration Number >

<MAM Registration Number >

# Authorisation to undertake the setting and sealing of meter regulators and any associated pressure control devices on a low pressure (LP) non standard meter installation or higher pressure meter installation with a metering pressure of 21mbar.

Thank you for completing the Request for Authorisation dated <

> applicable to the following:

MPRN:

Address: Note: this Authorisation only applies to the job address detailed above.

Following our review I can confirm that we have authorised your organisation to break the seal and to set and seal the meter regulator in accordance with the following conditions.

The regulator shall be set to ensure a metering pressure of	21 mbar.
The regulator lock up pressure shall not exceed	30 mbar.
The relief valve shall be set to open at a pressure of	35 mbar (not applicable to LP).
The final safety device shall be set at a pressure of	47.5 mbar (not applicable to LP)

Under all circumstances, including zero flow, the meter installation shall protect the installation pipe work, gas fittings and any appliances from pressures greater than 50 mbar.

The meter installation & housing shall be designed and installed or modified to comply with the requirements of IGE/GM/8 and shall be clearly labelled with the metering pressure.

The meter regulator, pressure control & protection devices and by-pass (where fitted) shall be sealed immediately after any setting or adjustment with a suitable seal within the meaning of the Gas Safety (Installation and Use) Regulations. The seals shall bear the OAMI registration number of your organisation or nominated OAMI.

This Authorisation specifically excludes any validation that the meter satisfies obligations under the Gas Act, Common Law Contract or other with respect to the meter being of a type appropriate for registering the quantity of gas supplied and it's installation in the premises. The responsibility of any design to meet the design objectives stated in your 'Request for Authorisation' and any other statutory obligations will remain with the OAMI acting on behalf of the meter owner as defined in the Gas Act 1986 (as amended 1995) Schedule 2B.

The following reference number has been allocated to this Authorisation, which should be quoted in any subsequent correspondence.

Yours sincerely

Letter E4B

GT Reference number:

<GT Address>

< Application reference number> <Date>

<Name & Address of MAM>

<Name & Address of OAMI (if different)>

<OAMI Registration Number >

<MAM Registration Number >

# Authorisation to undertake the setting and sealing of meter regulators and any associated pressure control devices on a low pressure (LP) non standard meter installation or higher pressure meter installation with a metering pressure other than 21mbar.

Thank you for completing the Request for Authorisation dated < > ap

> applicable to the following:

MPRN:

Address: Note: this Authorisation only applies to the job address detailed above.

Following our review I can confirm that we have authorised your organisation to break the seal and to set and seal the meter regulator in accordance with the following conditions.

The regulator shall be set to ensure a metering pressure of	[	] mbar.
The regulator lock up pressure shall not exceed	[	] mbar.
The relief valve shall be set to open at a pressure of	[	] mbar (not applicable to LP).
The final safety device shall be set at a pressure of	[	] mbar (not applicable to LP)

Under all circumstances, including zero flow, the meter installation shall protect the installation pipe work, gas fittings and any appliances from pressures greater than [11] mbar.

The meter installation & housing shall be designed and installed or modified to comply with the requirements of IGE/GM/4, IGE/GM/8 and shall be clearly labelled with the metering pressure, slam shut and creep relief setting.

The meter regulator, pressure control & protection devices and by-pass (where fitted) shall be sealed immediately after any setting or adjustment with a suitable seal within the meaning of the Gas Safety (Installation and Use) Regulations. The seals shall bear the OAMI registration number of your organisation or nominated OAMI.

This Authorisation specifically excludes any validation that the meter satisfies obligations under the Gas Act, Common Law Contract or other with respect to the meter being of a type appropriate for registering the quantity of gas supplied and it's installation in the premises. The responsibility of any design to meet the design objectives stated in your 'Request for Authorisation' and any other statutory obligations will remain with the OAMI acting on behalf of the meter owner as defined in the Gas Act 1986 (as amended 1995) Schedule 2B.

The following reference number has been allocated to this Authorisation, which should be quoted in any subsequent correspondence.

Yours sincerely

#### Letter F Failure to obtain Authorisation to set & seal regulators.

GT Reference number:

<GT Address>

< Application reference number> <Date>

<Name & Address of MAM>

<Name & Address of OAMI (if different)>

<OAMI Registration Number >

<MAM Registration Number >

## Notification of failure to obtain an Authorisation to undertake the setting and sealing of meter regulators, pressure control & protection devices on meter installations.

Thank you for completing the Request for Authorisation, dated <

>applicable to the following:

Generic request:\*

Job specific: MPRN\* \*delete as appropriate

Following our review of your application I have to inform you that your Request for Authorisation has not been approved for the following reasons:

The following reference number has been allocated to this Request for Authorisation which should be quoted in any subsequent correspondence.

You are invited to re-submit your request once the issues outlined above have been addressed.

Yours sincerely

#### Letter G1 Meter housing/accommodation approval letter.

GT Reference number:

<GT Address>

< Application reference number> <Date>

<Name of applicant>

<Address>

<OAMI Registration Number (if applicable) >

<Name of Responsible Engineer>

<Address>

<Site name and address or state GENERIC request>

Thank you for completing the Request for Approval dated < >.

<Insert GT name> has undertaken an appraisal of the proposed meter housing/accommodation on the basis of the information submitted. The housing/accommodation meets our requirements and therefore is approved.

It should be noted that 'approval' does not confer or imply granting of planning permission. The obtaining of planning permission, where needed, is the responsibility of the consumer/housing designer.

Approval does not imply the durability of any housing, or that the meter installation is appropriate for use. Where a purpose-designed enclosure is provided, including those within the main building, it shall not be used for purposes other than governing and metering the gas supply except as specifically allowed in the relevant meter installation design standards.

Yours sincerely

Letter G2 Meter housing/accommodation rejection letter.

GT Reference number:

<GT Address>

<Date>

<Name of applicant>

<Address>

<OAMI Registration Number (if applicable) >

<Name of Responsible Engineer>

<Address>

<Site name and address or state GENERIC request>

Thank you for completing the Request for Approval dated < >.

<Insert GT name> have undertaken an appraisal of the proposed meter housing/accommodation described above. The housing/accommodation does not meet our requirements for the following reasons:

You are invited to submit a request for approval once the issues outlined above have been addressed.

Yours sincerely

#### **APPENDIX I: Pressure control arrangements.**

# Acceptable pressure control and protection arrangements and operational pressures at the outlet of the meter regulator and any associated pressure control and protection device(s).

This appendix provides details of pressure control and protection arrangements and;

- the operational pressure settings for meter regulators and
- any associated pressure control and protection device(s),

This information should be used when making a 'Request for Authorisation'.

When an installer proposes to provide alternative pressure control and protection arrangements, full details of their proposals should be included within any 'Request for Authorisation'.

#### Refer to Table 5 and IGE/GM/8

#### Gas supply arrangements.

Pipes within the GT's network are designed both to provide the capacity requirement expected to occur in extreme conditions and to operate within specified pressure ranges such that the integrity of the pipes is maintained, and to ensure that a suitable pressure is available at the outlet of the ECV, for the safe operation of any gas appliance which a consumer could be reasonably expected to operate.

GT's assign pipes within their network to pressure tiers. Table 4 shows the standard operational pressures and the maximum design pressures that may occur at the outlet of the ECV, which terminates the gas supply pipe on a specific pressure tier.

These pressures should be used in the design and specification of the meter installation and when making a 'Request for Authorisation'.

In some circumstances there may be a requirement for the lowest operating pressure to be a higher value than that stated in Table 4. The Unified Network Code makes provision for an enhanced pressure service through a gas supply ancillary agreement between the GT and the registered system user (gas shipper).

Where an installer considers that an enhanced pressure service is appropriate they should contact the relevant registered system user.

Where it is identified (either from the information provided by the GT or the label on the service valve) that the capacity of a supply pipe is not consistent with gas users requirements, the meter installer should discuss this with the gas user who should arrange through their Gas Supplier for an increase in supply capacity.

#### TABLE 4: NETWORK PRESSURE TIERS.

Pressure Tier	OPERATIONAL	PRESSURES AT T THE ECV	DESIGN PRESSURES AT THE OUTLET OF THE ECV			
	DESIGN MINIMUM PRESSURE (DMP)	LOWEST OPERATING PRESSURE (LOP)	MAXIMUM OPERATING PRESSURE (MOP)	DESIGN PRESSURE (DP)	DESIGN MAXIMUM INCIDENTAL PRESSURE (DMIP)	
Low	19 mbar	25 mbar See Note 1.	75 mbar	75 mbar	200 mbar	
Medium <sup>35</sup>	35 mbar	35 mbar	185 mbar	2.0 bar	2.7 bar	
Medium <sup>65</sup>	65 mbar	75 mbar	250 mbar	2.0 bar	2.7 bar	
Medium <sup>105</sup>	105 mbar	105 mbar	1.1 bar	2.0 bar	2.7 bar	
Medium <sup>180</sup>	180 mbar	180 mbar	1.6 bar	2.0 bar	2.7 bar	
Medium <sup>270</sup>	270 mbar	280 mbar	2.0 bar	2.0 bar	2.7 bar	
Intermediate	See Note 2	See Note 2	See Note 2	7.0 bar	9.31 bar	
High	See Note 2	See Note 2	See Note 2	See Note 2	MOP +10%	

**Note 1:** Operating pressures of 21.5 mbar may occur, during normal operation, at the outlet of the ECV on parts of low pressure networks. However experience has shown that low pressure meter installations will provide a satisfactory outlet pressure when designed for an inlet pressure of 25 mbar and a maximum pressure absorption of 4mbar determined at an inlet design minimum pressure. BS 6400:1, IGEM/GM/6 and IGE/GM/8 have/will use these design criteria and therefore 25 mbar is used in this table for consistency with these metering standards.

**Note 2:** On intermediate and high pressure Networks the applicant shall confirm with the GT the operational pressures at the outlet of the particular service pipe ECV.

TERM	ABREVIATION	DEFINITIONS
Design Minimum Pressure	DmP	The minimum pressure that may occur at the end of any service pipe at the time of system design flow rate under extreme gas supply and maintenance conditions.
Lowest Operating Pressure	LOP	The lowest pressure that may occur under normal operating conditions.
Maximum Operating Pressure	MOP	The maximum pressure at which a system can be operated continuously under normal operating conditions.
Maximum Incidental pressure	MIP	The maximum pressure which a system is permitted to experience under fault conditions, limited by safety devices.
Design Pressure	DP	The pressure on which design calculations are based.
Design Maximum Incidental Pressure	DMIP	The maximum pressure which a system is permitted to experience under fault conditions, limited by safety devices, when the system is operated at the design pressure.

#### TABLE 5. GUIDANCE ON METER INSTALLATION CATEGORIES.

			CATEGORY												
		1	1 2 3A 3B							4A					
Pressure	e tier	LP 0 < MOP <u>&lt;</u> 75m bar	MP MOP <u>≺</u> 2bar	MP 75mbar <mop <u>&lt;</u>2bar</mop 	LP 0 < MOP <u>&lt;</u> 75mbar	LP 0 < MOP <u>&lt;</u> 75mbar	LP 0 < MOP <u>&lt;</u> 75mbar	LP 0 < MOP <u>&lt;</u> 75mbar	MP 75mbar≺MOP <u>≺</u> 2bar	MP 75mbar <mop <u>&lt;</u>2bar</mop 	IP 2bar <mop<u>&lt;7 bar (legacy domestic only)</mop<u>		IP 2bar <mop<u>&lt;7 bar</mop<u>	HP Above 7bar	
Сарас	city	<u>&lt;</u> 6m³/hr	<u>≺</u> 6m³/hr	<u>&lt;</u> 6m³/hr	6 <q<u>&lt;40m³/hr</q<u>	6 < Q <u>&lt;</u> 1076m³/hr	0 < Q <u>&lt;</u> 1076m³/hr	Q > 1076m³/hr	6 < Q <u>&lt;</u> 200m³/hr	200 < Q <u>&lt;</u> □m³/hr	0 <q<u>&lt;6m³/hr</q<u>	6 < Q <u>&lt;</u> 200m³/hr	200 < Q <u>&lt;</u> ⊡m³/hr	6 < Q <u>&lt;</u> ⊡m³/hr	
				Press	sure control a	nd protection	n devices								
Regular	tor(s)	Single stage- single stream BS6400-1			Single stage- single stream IGEM/GM/6	Single stage- single or twin stream IGEM/GM/6	Single stage- single or twin stream IGEM/GM/8	Single stage- single or twin stream IGEM/GM/8							
Regulator(s), incorporating pressure relief and excess flow shut off devices			Fig 1A BS6400-2												
Regulator(s), pressure relief (creep) and pressure activated slam shut				Fig 1B BS6400- 2					IGE/GM/8 Part 3 Table 1	IGE/GM/8 Part 3 Table 1		IGE/GM/8 Part 3 Table 1			
Monitor regulator plus active regulator, pressure relief (creep) and pressure activated slam shut												IGE/GM/8	IGE/GM/8	IGE/GM/8	
First stage active/monitor regulator and second stage active regulator, pressure relief (creep) and pressure activated slam shut												IGE/GM/8	IGE/GM/8	IGE/GM/8	
Operational pressures at the	outlet of the pressure con fitted the maximum opera												network a	nd where	
Regulator control	Pressure	21mbar	21mbar	21mbar	21mbar	21mbar	21mbar	21mbar	21mbar	21mbar	21mbar	21mbar	21mbar	21mbar	
Regulator	lockup	30m bar	30m bar	30m bar	30mbar	30m bar	30m bar	30m bar	30m bar	30m bar	30mbar	30m bar	30m bar	30m bar	
Additional final protecti	on device required?	NO	Yes	Yes	No	No	No	No	Yes	Yes	Yes	Yes	Yes	Yes	
Relief valve	opening		35m bar +3.5	35m bar + 3.5					35m bar + 3.5	35m bar + 3.5	35m bar +	35m bar +	35mbar +	35mbar +	
Final safety dev	ice operation		40m bar (Max)	47.5mbar + 2.5					47.5m bar + 2.5	47.5mbar + 2.5	47.5m bar + 2.5	47.5m bar + 2.5	47.5m bar + 2.5	47.5mbar + 2.5	
The meter installer shall de inter stage setting on 2 sta												Yes	Yes	Yes	

Additional requirements where 'Non-standard' appliances are used on Cat 4 installations: Regulator set pressure shall be consistent with appliance manufacturers instructions for normal operating pressure. Lock up pressure shall limit any temporary operating pressure; Relief valve shall be set to open at a pressure between regulator lock up and slam shut setting (it's setting shall not cause nuisance venting or inadvertant firing of the slam shut valve).

Slam shut shall be set to operate at a pressure higher than the relief valve setting and shall protect appliances and pipework from exceeding their tightness test pressure Note: For LP lock up pressure shall not exceed the appliance tightness test pressure as specified by the manufacturer.

#### **APPENDIX J: Addresses & WEB SITE links**

These addresses were correct at the time of writing, but are subject to change.

#### Energy Networks Association.

Web: www.energynetworks.org

Address: 6th Floor, Dean Bradley House, 52 Horseferry Road, London, SW1P 2AF

#### National Grid – Gas Distribution

Web: <u>www.nationalgrid.com/uk</u>

Email: networkstrategy.gt1andgt2@uk.ngrid.com

Address: Customer Support Team National Grid Gas, Brick Kiln Street, Hinckley. Leics, LE10 0NA.

#### Northern Gas Networks

Web: <u>www.northerngasnetworks.co.uk</u>

Email: <a href="mailto:connections\_gt1\_2\_3@northerngas.co.uk">connections\_gt1\_2\_3@northerngas.co.uk</a>

Address: 1100 Century Way, Thorpe Park Business Park, Colton, Leeds, LS15 8TU

#### Scotia Gas Networks

Web: www.sgn.co.uk

Email: gt1.gt2@sgn.co.uk

Address: St Lawrence House, Station Approach, Horley, Surrey, RH6 9HJ

#### Wales & West Networks

Web: www.wwutilities.co.uk

Email: GT2requests@wwutilities.co.uk

Address: Wales and West House, Spooner Close, Celtic Springs, Coedkernew, Newport, NP10 8FZ.

Ofgem web site: http://www.ofgem.gov.uk/ofgem/work/index.jsp?section=/areasofwork/metering#

## Independent Gas Transporters Association of Independent Gas Transporters (AIGT)

Web: <u>www.aigt.org.uk</u> Email: <u>john.barret@aigt.org.uk</u> Tel: 07790 877148

INEXUS Group : www.inexus.co.uk Email: <u>lenvoy gt@envoyonline.co.uk</u> Address: Driscoll Building No2, Ellen Street, Cardiff, CF10 4BQ

<u>GTC Pipelines Ltd</u> – <u>www.gtc-uk.co.uk</u> Representing GTC Pipelines and Utility Grid Installations

<u>E. S. Pipelines Ltd</u> - <u>www.espipelines.com</u> Representing ES Pipelines, ESP Networks, ESP Pipelines and ESP Connections

SSE Pipelines Ltd - www.scottish-southern.co.uk

Energetics Gas Ltd - www.energetics-uk.com

British Gas Pipelines Ltd - www.centrica.co.uk

Fulcrum Pipelines Ltd - www.fulcrum.co.uk